


FACILITY MAINTENANCE



SPEED BUMPS & CAR STOPS



INDUSTRIAL FANS



FLOOR TAPE APPLICATORS



PICNIC TABLES & BENCHES



BUILDINGS & SHELTERS



INDUSTRIAL & COMMERCIAL SIGNAGE

Speed Bumps & Car Stops R	52-55
Expand-A-Gates I	57
Industrial Fans & Air Conditioners R	57-60
Heaters R	60-62
Magnetic & Brush Sweepers I R	62-63
Floor Tape Applicators I	64
Acrylic Convex Mirrors R	65
Picnic Tables & Benches R I	66-67
Trash Receptacles R	68-69
Bicycles & Bicycle Racks V R I	71
Hose Reels R I	72-73
Warning Sirens I	73
Buildings & Shelters V I	74-75
Storage Lockers I	76-77
Fuel Pumps R	77-78
Sign Bases R I	79
Industrial & Commercial Signage V	80-92

SAFETY SIGN IDEAS



model YGR-LO-10-SI*

- (2) 120"L Rails
- (2) 42"H Posts
- Drop-In Style
- Powder Coat Finish



model VDKR-8-SI

- Size: 96"L x 42"H x 21" Midrail
- Powder Coat Finish
- Sockets Sold Separately



model SI-FD-10100

- Adhesive Floor Decal
- Decal Size: 36"W x 30"L
- Place in Front of Electrical Panels
- Custom artwork available



model BOL-SQ-42-4-SI

- Square Design
- Post Size: 4"
- Height: 42"
- Powder Coat Finish




model DCBB-42-4.5-SI

- Post Size: 42"H x 4.5"D
- Chain Length: 127"
- Removable Chain
- Powder Coat Finish



model ST-GR-4-SI*

- (1) 48"L Drop-In Guard Rail
- (2) 18"H Posts
- Powder Coat Finish



model LPRO-48-9-4-SI

- Length: 48"
- Height: 9"
- Diameter 4"
- Powder Coat Finish



model CG-42-SI

- Height: 42"
- Inside Size: 10¹³/₁₆"W x 10¹/₈"D
- Powder Coat Finish



model ADKR-8-SI

- Aluminum Construction
- 96"L x 42"H x 21" Midrail
- Sockets Sold Separately



model HRAIL-9072-SI*

- Galvanized Finish
- (1) 90" x 72" Starter
- (2) Bases



model BOL-MB-42-5.5-SI**

- Adhesive Label
- Height: 42"
- Diameter: 5¹/₂"
- 10" Wheels



model GGR-B-8-SI*

- Galvanized Finish
- Bolt-On Style
- (2) 96"L Rails
- (2) 42"H Posts


- All signs are made of aluminum composite. Material is comprised of two pre-painted sheets of 0.130" aluminum with a solid polyethylene core. Ideal for both indoor and outdoor use.
- Signs measure 14½" wide by 10½" high.
- **Customize the sign text to meet your specification.**
- Signs are manufactured with ultraviolet inks and anti-graffiti coating.
- Each sign includes predrilled holes and hardware.

*Sold in bundles.

**Utilizes adhesive label.



model HPRO-M-36-36-2-SI



model TEGC-24-36-2-SI



model PRAIL-102-Y-SI



model JBOL-36-12-SI**



model HPRO-48-42-4-SI



model BCD-7636-OR-SI



model GR-D-8-PC-YEL-SI*



model SQ-72-SI



model BOL-42-4.5-SI**



model PREG-42-SI



model BOL-FD-36-Y-SI



model CGP-36-SI




48 Hours
to Ship

model MPG-C



model MPG-E





model MPG-T

model MPG-L

Modular Guard Curbs

Modular Guard Curbs may be used in hundreds of applications for protecting rack and machinery. These innovative guards feature sloped sides and ends for better protection. Great for use indoors or out, units install easily with the concrete installation hardware (available separately). Bright yellow finish helps attract attention.

MODEL NUMBER	STYLE	OVERALL SIZE (L x D x H)	BOLT HOLES	NET WT. (POUNDS)	LIST PRICE EACH
MPG-C	CENTER SECTION	21 1/4" x 6" x 5"	2	15	\$46.00
MPG-E	END SECTION	21 1/4" x 6" x 5"	2	15	46.00
MPG-T	T-SECTION	12" (8 3/4"L) x 6" x 5"	1	13	39.00
MPG-L	L-SECTION	8 3/4" (8 3/4") x 6" x 5"	1	10	29.00
MPG-ABK-1	CONCRETE ANCHOR KIT (FOR MPG-T & MPG-L)			1	\$6.10
MPG-ABK-2	CONCRETE ANCHOR KIT (FOR MPG-C & MPG-E)			1	\$15.20




48 Hours
to Ship

Steel Dome Markers

Provide visible lane indication with these rugged Steel Dome Markers. Each unit has a pre-drilled hole in each corner for easier application. Mounting holes are 1/2" in diameter. Hardware sold separately.

MODEL NUMBER	OVERALL SIZE (W x L x H)	DOMES DIAMETER	CARTON QUANTITY	FINISH	WEIGHT (POUND)
DSB-6Y	7" x 7" x 2 1/2"	5 1/2"	6	POWDER COAT	12
AS-383-4PK	3/8" x 3" PACKAGE OF FOUR CONCRETE ANCHORS				2



model SBRY-72-A



model SBRY-CAP-A

48 Hours
to Ship

Molded Rubber Speed Bumps

Heavy-duty molded rubber construction for durability. Rubber includes UV stabilizer for longer life. Features five reflective yellow diagonal strips and "cats eyes" per side for better visibility. Four mounting holes per speed bump with one mounting hole per end cap, hardware included. Maximum capacity is 40,000 pounds.

MODEL NUMBER	OVERALL SIZE (W x L x H)	TYPE	TYPE OF HARDWARE KIT INCLUDED	WEIGHT (POUND)
SBRY-72-C	11 3/4" x 72" x 1 3/4"	SPEED BUMP	CONCRETE	53
SBRY-CAP-C	11 3/4"W x 11 3/4"L	END CAPS	CONCRETE	7
SBRY-72-A	11 3/4" x 72" x 1 3/4"	SPEED BUMP	ASPHALT	55
SBRY-CAP-A	11 3/4"W x 14 1/2"L	END CAPS	ASPHALT	7

Speed Bumps

Help control drivers in dangerous, areas while protecting people and property. One person installation. Can be removed for seal coating, snow removal, or change of location. Resists marring by oil, road salt, sunlight, and chemicals. Feature dual 1"W x 3/4"H cable channels and includes hardware. Constructed of lightweight recycled plastic. Compression strength is 3,200 pounds per square inch. The concrete hardware kit includes bolts, anchors, and washers. Asphalt kit includes spikes and butyl tape. The HD asphalt kit includes anchors and bolts. The HD anchor should be epoxied (epoxy not included) into the ground and then the speed bump is secured to that anchor with a bolt. The glue down anchor plate kit includes anchor plates, T-nuts, bolts, and washers. Requires 2-3 ounces of either 2-part epoxy or heavy duty construction adhesive to the bottom of each anchor plate, which is not included.



MODEL NUMBER	OVERALL SIZE (W x L x H)	TYPE OF HARDWARE KIT INCLUDED	NUMBER OF MOUNTING HOLES	WEIGHT (POUND)
SB-48Ⓢ	10" x 48" x 2"	CONCRETE	3	17
SBA-48Ⓢ	10" x 48" x 2"	ASPHALT	3	19
SBHA-48Ⓢ	10" x 48" x 2"	HD ASPHALT	3	19
SBG-48Ⓢ	10" x 48" x 2"	GLUE-DOWN	3	17
SBD-48*Ⓢ	12" x 48" x 2 1/4"	CONCRETE	3	26
SBDA-48*Ⓢ	12" x 48" x 2 1/4"	ASPHALT	3	29
SBDHA-48*Ⓢ	12" x 48" x 2 1/4"	HD ASPHALT	3	29
SBDG-48*Ⓢ	12" x 48" x 2 1/4"	GLUE-DOWN	3	26
SB-36Ⓢ	10" x 72" x 2"	CONCRETE	4	26
SBA-36Ⓢ	10" x 72" x 2"	ASPHALT	4	29
SBHA-36Ⓢ	10" x 72" x 2"	HD ASPHALT	4	28
SBG-36Ⓢ	10" x 72" x 2"	GLUE-DOWN	4	26
SBD-72Ⓢ	12" x 72" x 2 1/4"	CONCRETE	4	40
SBDA-72Ⓢ	12" x 72" x 2 1/4"	ASPHALT	4	43
SBDHA-72Ⓢ	12" x 72" x 2 1/4"	HD ASPHALT	4	43
SBDG-72Ⓢ	12" x 72" x 2 1/4"	GLUE-DOWN	4	40
SB-108Ⓢ	10" x 106" x 2"	CONCRETE	5	39
SBHA-108Ⓢ	10" x 106" x 2"	HD ASPHALT	5	45
SBG-108Ⓢ	10" x 106" x 2"	GLUE-DOWN	5	39
SBS-1012Ⓢ	REFLECTIVE SPEED BUMP SIGN			2
SBE-12**	END CAPS FOR STANDARD SPEED BUMPS			9

*Models do not have cable channels.
 **End caps only work with 10" W x 2" H sized speed bumps
 See additional anchor kits below.

48 Hours to Ship




Features dual 1" x 3/4" cable channels



SBD-48, SBDA-48, SBDHA-48, & SBDG-48 do not have cable channels.



REFLECTIVE SPEED BUMP SIGN model SBS-1012




Speed Bump Anchor Kits

Speed Bump Anchor Kits are a great addition to the facility maintenance department. The kit supplies a solution to securing speed bumps to a surface. The unit is designed of a strong construction that is resilient and long lasting throughout the harshest environments. Once the anchoring is in place, the speed bumps are ready for use. The kit is available in both glue down and asphalt anchor style.



model SB-72-AK


SPEED BUMP OPTIONS			
MODEL NUMBER	DESCRIPTION	USE WITH # OF HOLES	WEIGHT (POUND)
SB-48-AKⓈ	ASPHALT KIT FOR 48 MODELS	3	4
SB-36-AKⓈ	ASPHALT KIT FOR 36 MODELS	4	5
SB-108-AKⓈ	ASPHALT KIT FOR 108 MODELS	5	6
SB-HD-AK-3Ⓢ	HEAVY DUTY ASPHALT HARDWARE KIT	3	7
SB-HD-AK-4Ⓢ	HEAVY DUTY ASPHALT HARDWARE KIT	4	9
SB-HD-AK-5Ⓢ	HEAVY DUTY ASPHALT HARDWARE KIT	5	10
SB-48-GDKⓈ	GLUE DOWN KIT FOR 48 MODELS	3	2
SB-36-GDKⓈ	GLUE DOWN KIT FOR 36 MODELS	4	3
SB-108-GDKⓈ	GLUE DOWN KIT FOR 108 MODELS	5	3



model SB-48-GDK




48 Hours to Ship




Rubber Speed Humps

Rubber Speed Humps control traffic and reduce vehicle speeds. Ideal in neighborhoods, construction areas, hospitals, post offices, and airports. Can be removed for seal coating, snow removal, or change of location. Easy tongue and groove installation. Constructed of recycled and virgin rubber. Unit is black with yellow embedded highway tape to ensure high visibility. Complete modules include (5) five middle and (2) two end sections.



model RSH-108-24-C



model RSH-108-24-A




48 Hours
to Ship



model RSH-108-EF-C
FEMALE END CAP



model RSH-108-EM-C
MALE END CAP




model RSH-108-M-A
MIDDLE SECTION

MODEL NUMBER	OVERALL SIZE (W x L x H)	DESCRIPTION	TYPE OF HARDWARE KIT INCLUDED	UNIFORM CAPACITY	REDUCE SPEEDS (MPH)	WEIGHT (POUND)
DELUXE RUBBER SPEED HUMPS						
RSH-108-24-C	23 ¹ / ₂ " x 108" x 1 ³ / ₈ "	COMPLETE MODULE	CONCRETE	40,000 lb.	5-10	185
RSH-108-24-A	23 ¹ / ₂ " x 108" x 1 ³ / ₈ "	COMPLETE MODULE	ASPHALT	40,000 lb.	5-10	194
RSH-120-36-C	35 ¹ / ₄ " x 120" x 2 ⁷ / ₁₆ "	COMPLETE MODULE	CONCRETE	60,000 lb.	5-10	332
RSH-120-36-A	35 ¹ / ₄ " x 120" x 2 ⁷ / ₁₆ "	COMPLETE MODULE	ASPHALT	60,000 lb.	5-10	346
ADDITIONAL PIECES						
RSH-108-EF-C	23 ¹ / ₂ " x 8 ⁷ / ₈ " x 1 ³ / ₈ "	END CAP (female)	CONCRETE	40,000 lb.	5-10	12
RSH-108-EF-A	23 ¹ / ₂ " x 8 ⁷ / ₈ " x 1 ³ / ₈ "	END CAP (female)	ASPHALT	40,000 lb.	5-10	12
RSH-108-EM-C	23 ¹ / ₂ " x 9 ¹⁵ / ₃₂ " x 1 ³ / ₈ "	END CAP (male)	CONCRETE	40,000 lb.	5-10	12
RSH-108-EM-A	23 ¹ / ₂ " x 9 ¹⁵ / ₃₂ " x 1 ³ / ₈ "	END CAP (male)	ASPHALT	40,000 lb.	5-10	12
RSH-108-M-C	23 ¹ / ₂ " x 19 ⁹ / ₁₆ " x 1 ³ / ₈ "	MIDDLE SECTION	CONCRETE	40,000 lb.	5-10	23
RSH-108-M-A	23 ¹ / ₂ " x 19 ⁹ / ₁₆ " x 1 ³ / ₈ "	MIDDLE SECTION	ASPHALT	40,000 lb.	5-10	23
RSH-120-EF-C	35 ¹ / ₄ " x 10 ⁷ / ₁₆ " x 2 ⁷ / ₁₆ "	END CAP (female)	CONCRETE	60,000 lb.	5-10	22
RSH-120-EF-A	35 ¹ / ₄ " x 10 ⁷ / ₁₆ " x 2 ⁷ / ₁₆ "	END CAP (female)	ASPHALT	60,000 lb.	5-10	22
RSH-120-EM-C	35 ¹ / ₄ " x 11 ⁹ / ₁₆ " x 2 ⁷ / ₁₆ "	END CAP (male)	CONCRETE	60,000 lb.	5-10	22
RSH-120-EM-A	35 ¹ / ₄ " x 11 ⁹ / ₁₆ " x 2 ⁷ / ₁₆ "	END CAP (male)	ASPHALT	60,000 lb.	5-10	22
RSH-120-M-C	35 ¹ / ₄ " x 20 ⁵ / ₁₆ " x 2 ⁷ / ₁₆ "	MIDDLE SECTION	CONCRETE	60,000 lb.	5-10	56
RSH-120-M-A	35 ¹ / ₄ " x 20 ⁵ / ₁₆ " x 2 ⁷ / ₁₆ "	MIDDLE SECTION	ASPHALT	60,000 lb.	5-10	56


Rubber Speed Hump Anchor Kits

Anchor Kits are a great addition to the facility maintenance department. The kit supplies a solution to securing speed bumps to a surface. The unit is designed of a strong construction that is resilient and long lasting throughout the harshest environments. Once the anchoring is in place, the speed bumps are ready for use. The kit is available in both glue down and asphalt anchor style.



model RSH-GD-16

48 Hours
to Ship



MODEL NUMBER	DESCRIPTION	USE WITH LENGTH	WEIGHT (POUND)
RSH-108-HD-AK-KIT	HEAVY DUTY ASPHALT HARDWARE KIT	108"	8
RSH-120-HD-AK-KIT	HEAVY DUTY ASPHALT HARDWARE KIT	120"	8
RSH-GD-16	GLUE DOWN HARDWARE KIT	108"	6
RSH-GD-24	GLUE DOWN HARDWARE KIT	120"	9

Car Stops

Protect people and property from drivers in dangerous areas. Constructed of lightweight recycled plastic. One person installation. Can be removed for seal coating, snow removal, or change of location. Resists marring by oil, road salt, sunlight, and chemicals. Resists rotting, termite damage, and corrosion. No costly painting or maintenance. Asphalt kit includes spikes and butyl tape. The HD asphalt kit includes anchors and bolts. The HD anchor should be epoxied (epoxy not included) into the ground and then the speed bump is secured to that anchor with a bolt. The concrete hardware kit includes bolts, anchors, and washers. The glue down anchor plate kit includes anchor plates, T-nuts, bolts, and washers. Requires 2-3 ounces of either 2-part epoxy or heavy duty construction adhesive to the bottom of each anchor plate, which is not included. Hardware kits sold separately. Units feature notched out bottom surface for laying hoses or cords underneath. Models included in the CS-TB96 series are designed for use with trucks and other larger tired vehicles.



series CS-33



model CS-S24-B



model CS-S24-Y



model CS-S48-Y



model CS-S48-G



model CS-33-BL


48 Hours to Ship

Model CS-33-BL is made of black, recycled rubber.

MODEL NUMBER	OVERALL SIZE (W x L x H)	COLOR	NUMBER OF MOUNTING HOLES	WEIGHT (POUND)
CS-33-G	6" x 72" x 3 1/4"	GRAY	3	27
CS-33-Y	6" x 72" x 3 1/4"	YELLOW	3	27
CS-33-B	6" x 72" x 3 1/4"	BLUE	3	27
CS-33-W	6" x 72" x 3 1/4"	WHITE	3	27
CS-33-BL	5 3/4" x 71 3/4" x 4"	BLACK & YELLOW	4	37
CS-S24-G	6" x 24" x 3 1/4"	GRAY	2	10
CS-S24-Y	6" x 24" x 3 1/4"	YELLOW	2	10
CS-S24-B	6" x 24" x 3 1/4"	BLUE	2	10
CS-S24-W	6" x 24" x 3 1/4"	WHITE	2	10
CS-S48-G	6" x 48" x 4"	GRAY	2	22
CS-S48-Y	6" x 48" x 4"	YELLOW	2	22
CS-S48-B	6" x 48" x 4"	BLUE	2	22
CS-S48-W	6" x 48" x 4"	WHITE	2	22
CS-S72-G	6" x 72" x 4"	GRAY	3	33
CS-S72-Y	6" x 72" x 4"	YELLOW	3	33
CS-S72-B	6" x 72" x 4"	BLUE	3	33
CS-S72-W	6" x 72" x 4"	WHITE	3	33
CS-TB96-G	10" x 96" x 7"	GRAY	4	134
CS-TB96-Y	10" x 96" x 7"	YELLOW	4	134
CS-TB96-B	10" x 96" x 7"	BLUE	4	134
CS-TB96-W	10" x 96" x 7"	WHITE	4	134

For optional reflectors use suffix -RE

CAR STOP OPTIONS				
MODEL NUMBER	DESCRIPTION	USE WITH ABOVE NO. OF MOUNTING HOLES	WEIGHT (POUND)	
CS-AK-2	ASPHALT HARDWARE KIT	2	3	
CS-HD-AK-2	HEAVY DUTY ASPHALT HARDWARE KIT	2	2	
CS-33-KIT-2	CONCRETE HARDWARE KIT	2	2	
CS-GD-2	GLUE DOWN ANCHOR PLATE	2	2	
CS-AK-3	ASPHALT HARDWARE KIT	3	4	
CS-HD-AK-3	HEAVY DUTY ASPHALT HARDWARE KIT	3	3	
CS-33-KIT-3	CONCRETE HARDWARE KIT	3	2	
CS-GD-3	GLUE DOWN ANCHOR PLATE	3	3	
CS-AK-4	ASPHALT HARDWARE KIT	4	4	
CS-HD-AK-4	HEAVY DUTY ASPHALT HARDWARE KIT	4	4	
CS-33-KIT-4	CONCRETE HARDWARE KIT	4	2	
CS-GD-4	GLUE DOWN ANCHOR PLATE	4	3	



ASPHALT KIT model CS-AK

CONCRETE KIT model CS-33-KIT-3



GLUE DOWN KIT model CS-GD-2

CA Residents see WARNING B, Pg. 459

Heavy Duty Asphalt Anchors

Heavy Duty Asphalt Anchors are ideal for attaching items to an asphalt surface. The unit is designed of a strong construction that is resilient and long lasting throughout the harshest of environments. Once the anchors are in place, they promote safety and well-being by holding material in a secure position.

MODEL NUMBER	SHAFT DIAMETER	OVERALL DIAMETER	OVERALL LENGTH	QUANTITY	WEIGHT (POUND)
AS-HDA-12	1"	1 5/8"	12"	1	1
AS-HDA-12-4PK	1"	1 5/8"	12"	4	4
AS-HDA-12-6PK	1"	1 5/8"	12"	6	6



model AS-HDA-12-6PK

48 Hours to Ship



model CLB-5-78L



Clearance Bars

Clearance Bars are low maintenance, highly visible, and simple to read. These easy to install clearance bars are made of 1/4" nominal wall lo-density polyethylene. Comes with eye hooks attached, chain not included. Standard lettering is "CLEARANCE" and specified height (15 character spaces, includes: spaces, dashes, and/or feet, inches symbols. Other colors, specified lettering and additional characters available, contact factory.

MODEL NUMBER	OUTSIDE DIAMETER	LENGTH	LETTERING	COLOR	WEIGHT (POUND)
CLB-5-78P	5 1/4"	78"	NO	YELLOW	18
CLB-5-78L	5 1/4"	78"	YES	YELLOW	18
CLB-7-110P	7 1/2"	110"	NO	YELLOW	85
CLB-7-110L	7 1/2"	110"	YES	YELLOW	85



ECONOMY WARNING BARRIER • model ODG-121-F



DELUXE WARNING BARRIER • model ODG-133-BL

Overhead Door Warning Barriers



Protect overhead doors from fork truck damage. Heavy-duty PVC construction is lightweight and will not rust. Highly visible black and yellow safety stripes and two American flags serve as a visual warning. Includes two 15' long chains with quick connects to hang barrier from ceiling or existing overhead door track.


Model ODG-133-BL features built-in warning sirens and flashing lights that activate when the barrier is bumped or contacted. Provides an audible and visual warning before damage to overhead door is caused. 76 DB at 9 feet. Requires (4) four 9V lithium batteries, not included.

MODEL NUMBER	DESCRIPTION	OVERALL LENGTH	WEIGHT (POUND)
ODG-121-F	ECONOMY WARNING BARRIER	120"	63
ODG-133-BL	DELUXE WARNING BARRIER	120"	66



model MPG-C

model MPG-E




model MPG-T

model MPG-L

Modular Guard Curbs

Modular Guard Curbs may be used in hundreds of applications for protecting rack and machinery. These innovative guards feature sloped sides and ends for better protection. Great for use indoors or out, units install easily with the concrete installation hardware (available separately). Bright yellow finish helps attract attention.

MODEL NUMBER	STYLE	OVERALL SIZE (L x D x H)	BOLT HOLES	NET WT. (POUNDS)
MPG-C	CENTER SECTION	21 1/4" x 6" x 5"	2	15
MPG-E	END SECTION	21 1/4" x 6" x 5"	2	15
MPG-T	T-SECTION	12" (8 3/4"L) x 6" x 5"	1	13
MPG-L	L-SECTION	8 3/4" (8 3/4") x 6" x 5"	1	10
MPG-ABK-1	CONCRETE ANCHOR KIT (FOR MPG-T & MPG-L)			1
MPG-ABK-2	CONCRETE ANCHOR KIT (FOR MPG-C & MPG-E)			1



model MHGR-32

Manhole Guard Rail

The manhole guard rail is perfect for utility maintenance and city officials. The simple set up and take down promotes quick use when on the go and a compact storage when not in use. High rails and an attaching chain limit access and promote safety to the worker in the enclosed area. A brightly colored high strength construction makes the unit highly visible, giving caution to pedestrians and other workers to keep their distance.

MODEL NUMBER	OVERALL SIZE (W x L x H)	USABLE SIZE (W x L)	WEIGHT (POUND)
MHGR-32	33 5/8" x 32 5/8" x 44 1/8"	31" x 30"	105

Expand-A-Gates

Designed to set up quickly and easily wherever and whenever they are needed. Ideal for preventing potential accidents. Lightweight design allows personnel to quickly retrieve the gate and limit access to unsafe areas. Smooth operating scissor action. Interlocking and nestable. Suffix -C features casters. Suffix -W features one swivel caster with a wall/rack mounting kit. Model PEXGATE is constructed of heavy-duty molded yellow and black plastic. One side of gate includes reflectors for better visibility. End pieces are hollow and may be filled with liquid for added weight. Assembly required.



model EXGATE-30



STEEL CONSTRUCTION



ALUMINUM CONSTRUCTION
model ALEXGATE-30-C

MODEL NUMBER	OVERALL COLLAPSED WIDTH	EXPANDED GATE WIDTH	*OVERALL HEIGHT	WEIGHT (POUND)
STEEL CONSTRUCTION				
EXGATE-30 [®]	19¾"	139"	38"	55
EXGATE-30-C [®]	19¾"	139"	40⅛"	57
EXGATE-30-W [®]	20 ⁵ / ₁₆ "	139"	38 ⁵ / ₁₆ "	61
EXGATE-W-KIT	WALL MOUNT KIT			5
ALUMINUM CONSTRUCTION				
ALEXGATE-30 [®]	19¾"	139"	38"	25
ALEXGATE-30-C [®]	19¾"	139"	40⅛"	30
ALEXGATE-30-W [®]	20 ⁵ / ₁₆ "	139"	38 ⁵ / ₁₆ "	34
ALEXGATE-W-KIT	WALL MOUNT KIT			5
PLASTIC CONSTRUCTION				
PEXGATE-30 [®]	11½"	122"	38"	12
PEXGATE-30-C [®]	11½"	122"	40¾"	13

*OVERALL HEIGHT WHEN COLLAPSED



model EXGATE-30-W




Connector for wall mounted unit



Plastic unit is easy to fill for added weight



model PEXGATE-30



PLASTIC CONSTRUCTION
model PEXGATE-30-C

Industrial Duty Circulator Fans 115V 1-PHASE STANDARD

Two speed, 115V, 1 phase, ball bearing, totally enclosed and permanently lubricated Industrial Duty Circulator Fan. Pull chain switch with a 12 foot long cord and an SJT type 3 conductor cord. Meets OSHA standards and is ETL C/US listed. ¼ HP electric motor.

MODEL NUMBER	BLADE DIAMETER	MOUNTING STYLE	AMPS HIGH	CFM HIGH	CFM LOW	WEIGHT (POUND)
ICRF-24-P	24"	PEDESTAL	2.5	6800	5000	75
ICRF-24-W	24"	WALL	2.5	6800	5000	45
ICRF-30-P	30"	PEDESTAL	2.7	7900	6000	75
ICRF-30-W	30"	WALL	2.7	7900	6000	48
OSCILLATING STYLE						
ICRF-24-PO	24"	PEDESTAL	2.5	6800	5000	79
ICRF-24-WO	24"	WALL	2.5	6800	5000	49
ICRF-30-PO	30"	PEDESTAL	2.7	7900	6000	78
ICRF-30-WO	30"	WALL	2.7	7900	6000	53



model ICRF-24-P



Work Station Fans 115V 1-PHASE STANDARD

Three speed, 115V, 1 phase, totally enclosed, permanently lubricated motor Work Station Fan. Mount with one bolt or lag screw to walls, ceilings, work benches, machines or any surface. Pull chain switch on a 10 foot long SJT type 3 conductor cord. Meets OSHA standards and is ETL C/US listed.



MODEL NUMBER	BLADE DIAMETER	MOUNTING STYLE	AMPS HIGH	CFM HIGH	CFM MED	CFM LOW	WEIGHT (POUND)
WSF-12	12"	WALL	1.1	1650	1420	1120	17
WSF-18	18"	WALL	2.2	4600	4200	3200	26
WSF-18-F	18"	FLOOR	1.5	4600	4200	3200	23

High Performance Circulator Fans 115V 1-PHASE STANDARD

Two speed, 115V, 1 phase, ball bearing, totally enclosed, and permanently lubricated Industrial Duty Circulator Fan. Pull chain switch with a 12 foot long SJT type 3 conductor cord. Meets OSHA standards and is ETL C/US listed. 1/3 HP electric motor.



MODEL NUMBER	BLADE DIAMETER	MOUNTING STYLE	AMPS HIGH	CFM HIGH	CFM LOW	WEIGHT (POUND)
HPCR-30-P	30"	PEDESTAL	3.4	8200	6200	75
HPCR-30-W	30"	WALL	3.4	8200	6200	48
HPCR-30-I	30"	I-BEAM	3.4	8200	6200	51
HPCR-30-C	30"	CEILING	3.4	8200	6200	48

Portable Work Station Fan 115V 1-PHASE STANDARD

The three (3) speed, ball bearing, Portable Work Station Fan is totally enclosed and permanently lubricated. This fan has a rotary switch, 360° tilting head, 10 foot long SJT type 2 conductor cord, and coated steel guard. Steel hub/spider aluminum paddle blades and meets OSHA standards. Overall size is 25"W x 27"L x 53"H. ETL C/US listed.



MODEL NUMBER	BLADE DIAMETER	MOUNTING STYLE	CFM HIGH	CFM MEDIUM	CFM LOW	WEIGHT (POUND)
PWSF-18H-TE	18"	PEDESTAL	4600	4200	3200	35

Shutter Mounted Exhaust Fans 115V 1-PHASE STANDARD

Inside-building installation only with vents outside. Eliminate need for external framing and shutter. Ideally suited for thin wall buildings. Units are 115V, 1 phase totally enclosed and permanently lubricated. Pull chain switch. No cord. Junction box provided for direct wiring. Meets OSHA standards.



MODEL NUMBER	BLADE DIAMETER	MOTOR HP	AMPS HIGH	CFM HIGH	CFM MED	CFM LOW	WEIGHT (POUND)
SME-12	12"	1/12	1.1	825	710	560	16
SME-18	18"	1/8	2.2	2300	2100	1850	25
SME-24	24"	1/4	2.5	3400	---	2770	41
SME-30	30"	1/4	2.7	3950	---	3080	50

Direct Drive Portable Blower 115V 1-PHASE STANDARD

The two speed, 115V, 1 phase, ball bearing, Portable Blower has a totally enclosed motor. The fan also features 3 paddle style steel blades and 8" rubber wheels. It has a rocker switch with a 15' SJT type 3 conductor power cord. Meets OSHA standards. ETL C/US listed.




MODEL NUMBER	BLADE DIAMETER	RPM HIGH	AMP HIGH	CFM HIGH	CFM LOW	WEIGHT (POUND)
DDB-36	36"	1100	5.5	12500	9000	110

Commercial Circulator Fans **115V 1-PHASE STANDARD**

Two speed, 115V, 1 phase, ball bearing Commercial Circulator Fan. Pull chain switch with a 9 foot long cord and an SJT type 3 conductor cord. Meets OSHA standards and is UL C/US listed. ¼ HP electric motor. These Circulator Fans do not have a totally enclosed motor. They should be used in a clean and dry commercial application.

MODEL NUMBER	BLADE DIAMETER	MOUNTING STYLE	AMPS HIGH	CFM HIGH	CFM LOW	WEIGHT (POUND)
CCRF-24-P	25"	PEDESTAL	2.3	5400	4300	63
CCRF-24-W	25"	WALL	2.3	5400	4300	43
CCRF-30-P	30"	PEDESTAL	2.4	6000	4800	66
CCRF-30-W	30"	WALL	2.4	6000	4800	46



model CCRF-30-W

model CCRF-30-P

Commercial Belt Drive Portable Blower **115V 1-PHASE STANDARD**

The two speed, ball bearing Commercial Circulator Fan is pull chain. Meets OSHA standards and is UL C/US listed. This fan does not have a totally enclosed motor and should be used in a clean and dry commercial application. Features 8 foot long SJT type 3 conductor cord and 8" rubber wheels.

MODEL NUMBER	BLADE DIAMETER	AMP HIGH	CFM HIGH	CFM LOW	WEIGHT (POUND)
DDB-C-42	42"	6.5	13500	11000	93




model DDB-C-42

Commercial Direct Drive Blowers **115V 1-PHASE STANDARD**

Two speed, 1/3 HP, 115V, 1 phase, ball bearing motor, permanently lubricated. Rocker switch (MB-C-30) or rotary switch (MB-RS-C-36) standard. 6 foot long SJT type 3 conductor cord. Meets OSHA standards and is UL listed. These Direct Drive Blowers do not have a totally enclosed motor. They should be used in a clean and dry commercial application.

MODEL NUMBER	BLADE DIAMETER	AMPS HIGH	CFM HIGH	CFM LOW	TYPE	WEIGHT (POUND)
MB-C-30	30"	3.6	6300	5500	SWIVEL	60
MB-RS-C-36	36"	3.6	8200	7000	STATIONARY	70



model MB-C-30

model MB-RS-C-36

Commercial Floor Fans **115V 1-PHASE STANDARD**

Three speed, 115V, 1 phase, permanently lubricated motor, with rotary switch and 7 foot long SJT type 3 conductor cord. Meets OSHA standards and is UL listed. These floor fans do not have a totally enclosed motor. They should be used in a clean and dry commercial application.

MODEL NUMBER	BLADE DIAMETER	MOTOR HP	CFM HIGH	CFM MED	CFM LOW	WEIGHT (POUND)
FF-C-12	12"	1/12	2100	1750	1500	10
FF-C-20	20"	1/5	3450	3100	2950	18



model FF-C-20

Industrial Ceiling Fans **115V 1-PHASE STANDARD**

Lower winter heating costs by recovering residual heat trapped at roof level. Fully assembled except blade bolt down, 3 conductor power cord is 3 foot long with plug. All metal construction, with white epoxy finish and aluminum paddles. Fan has 18" down rod with safety cable. Speed controls and reversion switches available, please contact factory.

MODEL NUMBER	TYPE	SIZE	VOLTAGE / PHASE	CFM	WEIGHT (POUND)
ICF-48	DOWN DRAFT	48"	115V, 1PH	17000	13
ICF-56	DOWN DRAFT	56"	115V, 1PH	21000	17
ICF-56-R	REVERSIBLE	56"	115V, 1PH	21000	16



series ICF



Heavy-Duty Portable Evaporative Cooler

115V 1-PHASE STANDARD

These Portable Evaporative Coolers have large internal water reservoirs that allow units to operate approximately 8 hours without being connected to an external water source. Water is supplied to the internal tank from a standard 3/4" water hose or from optional water tank. Water level in internal tank is controlled by the unit's float valve. Maintenance free submersible water pump. 8" thick evaporative media pads are easily accessible for routine maintenance. Roto-molded corrosion free polyethylene housing. 20 foot long, 16 ga. 3 conductor cord with GFCI plug. Thermally protected, permanently lubricated fan motor. Variable 3 speed. Weather tight fan and pump control switches. 4" heavy-duty casters; two (2) locking, two (2) non-locking. ETL listed.

MODEL NUMBER	BLADE SIZE	MOTOR HP	UNIT AMPS	CFM	EFFECTIVE SQ. FEET	INTERNAL WATER TANK	OVERALL SIZE (W x L x H)	WEIGHT (POUND)
TS-EVAP-36HD	36"	0.7	15.0	12500	3125	60 gal.	67" x 34 1/2" x 77"	307



Variable Speed Air Curtains

These Heavy Duty Air Curtains can be used above entry doors and industrial warehouse doors to prevent loss of cool air and maintain a clean environment. These curtains contain a heavy duty 20 gauge rigid steel cabinet, with baked on epoxy powder coat paint for durability. Motor is a heavy duty, PSC, direct drive high efficiency, and signed for use with SCR controllers. Motors are permanently lubricated for long life and have thermal over load protection. SCR speed controller supplied on all units compatible with the motor with low end adjustment for air volume control and savings in power consumption. These heavy duty units have a 3/4 HP motor, 120V power and can go up to a 12' high doorway. Heating options available, contact factory.

MODEL NUMBER	DIMENSIONS WIDTH x HEIGHT	CFM (LOW x HIGH)	WEIGHT (POUND)
ACURT-36	36" x 16" (1 ACURT-36)	819 / 2672	77
ACURT-48	48" x 16" (1 ACURT-48)	906 / 4611	85
ACURT-60	60" x 16" (1 ACURT-60)	1126 / 5763	93
ACURT-72	72" x 16" (2 ACURT-36's)	1638 / 5344	154
ACURT-96	96" x 16" (2 ACURT-48's)	1812 / 9222	170
ACURT-108	108" x 16" (3 ACURT-36's)	2457 / 8016	231
ACURT-120	120" x 16" (1 ACURT-48 & 2 ACURT-36's)	2544 / 9955	239



Quartz Infrared Spot Heaters

1-PHASE STANDARD

Keep cool work areas well heated with these Infrared Heaters. The quartz tube radiates a blanket of heat in a 60° symmetrical pattern. Unit includes; gold aluminum reflector and end caps, mounting chains, S-hooks, and a cord set with plug. Units can be hung from the ceiling with mounting chains. Meets OSHA standards and is ETL C/US listed. Outdoor and indoor rated, outdoor use needs to be protected from the elements using a solid overhang.

MODEL NUMBER	WATTS	VOLTS	PHASE	BTU's	WEIGHT (POUND)
VCH-46C	1500	120	1	5120	9
VCH-57C	3000	240	1	10239	11
VCH-WG46	S.S. WIRE GUARDS (use with model VCH-46C)				2
VCH-WG57	S.S. WIRE GUARDS (use with model VCH-57C)				2



model CFFH-240



model FFH-118

model CRFH-198

Portable Electric Heaters

1-PHASE STANDARD

Portable Electric Heaters are lightweight and have an easy grip handle for convenience. These heaters are perfect for office, or small spot heating applications. They include a 6 foot long 3 conductor cord and temperature control thermostat. Model CFFH-240 has a 20 amp plug configuration, which is great for construction sites. Model FFH-118 and CRFH-198 meet OSHA standards and are ETL C/US listed, while CFFH-240 is only UL C/US listed. Indoor use only.

MODEL NUMBER	OVERALL SIZE (W x D x H)	NUMBER OF SETTINGS	VOLTAGE/PHASE	BTU's	WEIGHT (POUND)
FFH-118	10" x 9 1/2" x 16"	2 HEAT / 1 FAN	120, 1PH	5120	10
CRFH-198	11" x 12" x 15"	3 HEAT	120, 1PH	5120	10
CFFH-240	10 5/8" x 10" x 12 3/4"	2 HEAT	240/208, 1PH	13648	15

Portable Electric Salamanders

Portable Electric Salamanders are the perfect odorless, flameless, electric alternative to propane and kerosene space heaters. Safety yellow heater enclosures with safety screens on both air intake and output openings. The unit includes long-life finned tubular heating elements, thermostat adjustment, and a fan only operating feature. Includes access panel for direct wiring connections. Wheels and handle for easy portability over all surface types. Units are ETL C/US listed. Indoor use only.



model PES-1520-3

MODEL NUMBER	DESCRIPTION	KW AMPS	VOLTS PHASE	TEMP RISE	WEIGHT (POUND)
PES-1520-3	PORTABLE HEATER	15/42	208/3	45	65
PES-1524-1	PORTABLE HEATER	15/63	240/1	45	69
PES-1524-3	PORTABLE HEATER	15/36	240/3	45	69
PES-1548-3	PORTABLE HEATER	15/18	480/3	45	65
PES-3048-3	PORTABLE HEATER	30/36	480/3	90	83
PES-1024-1*	PORTABLE HEATER	10/42	240/1	30	63

*FACTORY PRE-WIRED WITH 10' CABLE & STRAIGHT BLADE RANGE PLUG

OPTIONAL 25 FOOT CORD WITH PLUG		
MODEL NUMBER	CABLE TYPE	USE WITH MODEL
PES-43-SO	4/3 SO, POWER CORD	PES-1524-1
PES-64-SO	6/4 SO, POWER CORD	PES-1520-3, PES-1524-3, PES-3048-3
PES-124-SO	12/4 SO, POWER CORD	PES-1548-3

Portable Electric Infrared Heaters 3-PHASE STANDARD

Provide instant, odor-free heat for indoor and semi-protected outdoor workstations and warehouse areas. Economical electric infrared heat warms only persons and objects, not the air volume. Durable heavy-duty flat panel emitter heating elements are designed for a variety of applications using no glass materials. All models have gold anodized aluminum reflectors, terminal box, protective wire screens, and reinforced front edge and corner construction. Heaters can be adjusted on the hand cart to operate in a horizontal or vertical position for maximizing the infrared heating pattern. Carts consist of a rugged steel design and are equipped with 6" rubber wheels and twin hand grips. Heaters are factory wired for three phase, but can be converted to single phase for most units.

MODEL NUMBER	WATTS	BTU's	VOLTS	PHASE	AMPS	WEIGHT (POUND)
VFSP-4324-3	4300	14,672	240	3	10.36	41
VFSP-4348-3	4300	14,672	480	3	5.18	41
VFSP-9524-3	9500	32,415	240	3	22.89	58
VFSP-9548-3	9500	32,415	480	3	11.44	58



model VFSP-4324-3

model VFSP-9548-3

Portable Infrared Heaters 220V 1-PHASE STANDARD

Radiant heat can be adjusted in distance and height. Adjustable brightness for various applications. Requires 220V single phase power supply @ 15 amps. Portable with four swivel casters (two with brakes). Timer is included for auto-shut off. Indoor use only.

MODEL NUMBER	MAXIMUM POWER OUTPUT	LAMP ELEMENTS	ELEMENT OVERALL SIZE (W x D x H)	ELEMENT EACH SIZE (W x D x H)	WEIGHT (POUND)
HEAT-S	2400 W	3	27" x 6" x 30"	23½" x 4¼" x 7¾"	105
HEAT-S1	2000 W	4	39" x 6" x 18"	17¾" x 4¼" x 7¾"	115
HEAT-S2	3000 W	6	39" x 6" x 30"	17¾" x 4¼" x 7¾"	135




model HEAT-S


Portable Quartz Infrared Spot Heater 115V 1-PHASE STANDARD

Portable heater adjusts from 2' to 6' in height. Wire guard is included, as well as a 15' cord set with plug (3 wire). Unit comes standard with four 2½" casters. Meets OSHA standards and is ETL C/US listed. Indoor use only.

MODEL NUMBER	WATTS	BTU's	VOLTS	PHASE	WEIGHT (POUND)
VCH-48-P	1500	5,120	115	1	30



model VCH-48-P



Portable Infrared Heat Panels

Portable Infrared Heat Panels are a great asset in cold work areas. Built to withstand industrial applications, such as auto collision repair shops. Units can be rolled easily to an array of areas without the need of additional personnel or lifting devices. The overall height allows the heat to expand more freely through out the workspace and quickly diminishes cold areas.

MODEL NUMBER	VOLTAGE	LAMP ELEMENTS	OVERALL SIZE (W x H x D)	HEATED AREA (W x H)	WEIGHT (POUND)
PIHP-4	240	4	44 ⁵ / ₈ " x 56 ¹ / ₂ " x 30"	40" x 44"	116
PIHP-6	240	4	66 ⁵ / ₈ " x 56 ¹ / ₂ " x 30"	61" x 44"	141
PIHP-11	240	7	66 ⁵ / ₈ " x 89 ¹ / ₂ " x 30"	61" x 77"	225



Manual Brush Sweepers

Use these sweepers anywhere, indoors or out, on concrete, asphalt, tile, and commercial carpets. Great for parking lots, gas stations, theaters, warehouses, schools, etc.

Model JAN-II is faster and more efficient than cleaning with conventional push brooms. The rotation of the wheels causes the brushes to rotate and pick up material. The side broom allows for cleaning along curbs, walls, and in corners. Contains no electric motor. Removable handle for storage is standard. Steel construction.

Model JAN-SM includes two (2) brushes on each front corner with a 1/4" overlap. A retractable handle is ideal for storage.

Model JAN-LG is a deluxe brush sweeper. The two (2) 11" diameter brushes, one on each front corner, come with independent 1/2" height adjustment. The bottom center brushes also features 1/2" height adjustment. Those brushes measure 17 1/2" x 5 1/2". A folding handle for easy storage is standard.



MODEL NUMBER	OVERALL SIZE (W x D x H)	SWEEPING AREA	CAPACITY (GALLONS)	POWERED	WEIGHT (POUND)
JAN-II ⊕	29" x 48" x 37 ⁷ / ₈ "	27"	10	BELT DRIVEN	81
JAN-SM ⊕	21 1/4" x 24" x 43"	22"	6	GEAR DRIVEN	20
JAN-LG ⊕	32 1/2" x 30" x 41 1/2"	32 1/2"	9	BELT DRIVEN	35

Magnetic Push Sweepers

Magnetic Sweepers are ideal for manufacturing facilities and construction sites. The sweeper is ergonomically friendly with an efficient handle controlled release. The design and capacity can accommodate large and small materials. While the standard handle allows for comfortable upright position during use, the wheels allow smooth rolling for quick and easy collection of objects.

Model MPSR-24-B and MPSR-36-B have a bent handle for more ergonomic handling.

Model TAM-30 is constructed of aluminum frame for lightweight strength. Other features include a telescoping handle for easy storage and length preference, a manual release for safe disposal, and a rotatable base for maneuverability.



MODEL NUMBER	REMOVAL PROCESS	SWEEP WIDTH	WEIGHT (POUND)
MFSR-18 ⊕	HANDLE RELEASE (on top of sweeper)	18"	14
MFSR-24 ⊕	HANDLE RELEASE (on top of sweeper)	24"	16
MFSR-30 ⊕	HANDLE RELEASE (on top of sweeper)	30"	21
MFSR-36 ⊕	HANDLE RELEASE (on top of sweeper)	36"	23
MPSR-24 ⊕	HANDLE RELEASE LEVER (on handle)	24"	35
MPSR-24-B ⊕	HANDLE RELEASE LEVER (on handle)	24"	40
MPSR-36-B ⊕	HANDLE RELEASE LEVER (on handle)	36"	51
TAM-30 ⊕	MANUAL RELEASE	3"	4

Fork Truck Mounted Brush Sweepers

Fork Truck Brush Sweepers are ideal for interior and exterior commercial sweeping. Great for cleanup applications; docks, warehouses, and parking lots. Lightweight aluminum body with polypropylene bristles. Powder coat finish. Attach unit by sliding forks into pockets and securing with locking screws.

Optional **Magnets** are a great asset to manufacturing and construction facilities. Enables the user to collect material in fewer passes. For best use, attach the magnet to the front of the existing broom and fasten to the forklift. Once in place, while traversing the desired area the magnet will detect metal items before they get caught in the bristles of the broom. Works with series VSWP and VPS.

The optional **Edge Markers** work with the deluxe brush sweeper series VPS. The 36" high markers are a visible indicator of the edge of the room for safety precautions. The units height allows the user to be informed while still maintaining the proper drive position.

Optional **Dust Mop** attaches to collect dust and fine particles on smooth floors. Works with series VSWP and VPS.


MODEL NUMBER	OVERALL SIZE (W x D x H)	FORK POCKET (W x D x H)	SWEEPING WIDTH	BRISTLE LENGTH	WEIGHT (POUND)
ECONOMY BRUSH SWEEPERS					
VSWP-48	48" x 5" x 9"	5" x 8" x 2"	48"	8"	43
VSWP-60	61" x 5" x 9"	5" x 8" x 2"	60"	8"	51
VSWP-48-RB	48" REPLACEMENT BRUSH KIT (5 ROWS TO A KIT)				18
VSWP-60-RB	60" REPLACEMENT BRUSH KIT (5 ROWS TO A KIT)				22
DELUXE BRUSH SWEEPERS					
VPS-60	60" x 16" x 12"	8 ³ / ₈ " x 15 ¹ / ₂ " x 2"	60"	11"	146
VPS-72	74" x 16" x 4 ¹ / ₂ "	8 ³ / ₈ " x 15 ¹ / ₂ " x 2"	72"	11"	173
VPS-60-RB	60" REPLACEMENT BRUSH KIT (8 ROWS TO A KIT)				60
VPS-72-RB	72" REPLACEMENT BRUSH KIT (8 ROWS TO A KIT)				70
OPTIONS					
VSWP-48-MG	4 FT. LONG MAGNET use with VSWP-48 & VSP-48				30
VSWP-60-MG	5 FT. LONG MAGNET use with VSWP-60 & VSP-60				37
VSP-EMK	EDGE MARKERS use with series VSP				1
VSWP-60-DM	DUST MOP ATTACHMENT use with VSWP-60 & VSP-60				10



model VSWP-48



model VPS-60



model VSWP-48-MG



model VSWP-60-DM



model VSP-EMK

Hanging Magnetic Sweepers

Hanging Magnetic Sweepers are ideal for cleaning industrial settings, parking lots, and loading areas. The design is durable, yet lightweight, for easy maneuverability and portability from work area to work area. A release lever on series MS and HFMS is located in the sweeper for simple, safe discarding of fragments. Constructed with heavy gauge steel and aluminum. Comes completely assembled.

Hanging Magnetic Sweepers, *Chain Hang-Type* with eyebolts and chains for hanging units from a vehicle.

Hanging Magnetic Sweepers *with Forklift Hang-Type* can be suspended from a fork lift for smooth and efficient gathering of material, both large and small. Fork pockets measure 5"W x 1¹/₄"H.

MODEL NUMBER	DESCRIPTION	SWEEP WIDTH	CAPACITY (POUND)	WEIGHT (POUND)
MAGNETIC HANG-TYPE SWEEPER				
MS-36	CHAIN HANG-TYPE	36"	45	23
MS-48	CHAIN HANG-TYPE	48"	55	28
MS-60	CHAIN HANG-TYPE	60"	65	34
MS-72	CHAIN HANG-TYPE	72"	75	39
MAGNETIC HANG-TYPE SWEEPER - HEAVY-DUTY				
HDMS-36	CHAIN HANG-TYPE	36"	75	36
HDMS-48	CHAIN HANG-TYPE	48"	100	55
HDMS-60	CHAIN HANG-TYPE	60"	120	68
HDMS-72	CHAIN HANG-TYPE	72"	130	79
MAGNETIC HANG-TYPE SWEEPER WITH FORK LIFT HANGER				
HFMS-36	FORKLIFT HANG-TYPE	36"	45	23
HFMS-48	FORKLIFT HANG-TYPE	48"	55	28
HFMS-60	FORKLIFT HANG-TYPE	60"	65	34
HFMS-72	FORKLIFT HANG-TYPE	72"	75	39
MAGNETIC HANG-TYPE SWEEPER WITH FORK LIFT HANGER - HEAVY-DUTY				
HDFMS-36	FORKLIFT HANG-TYPE	36"	75	44
HDFMS-48	FORKLIFT HANG-TYPE	48"	100	57
HDFMS-60	FORKLIFT HANG-TYPE	60"	120	71
HDFMS-72	FORKLIFT HANG-TYPE	72"	130	83


model MS-36




model HDMS-48



model HFMS-48



model HDFMS-36



48 Hours
to Ship



model TPA-10



model TPA-20

48 Hours
to Ship



Floor Tape Applicators & Floor Tape

Model TPA-10 - Designed to apply tape as you walk. Solid steel construction, comfortable hand grips, and durable rubber wheels allow for easy operation and maintenance. Features a soft rubber applicator head. Holds tape rolls with a 3" diameter core and widths between 1" minimum and 4" maximum.

Model TPA-20 - Applicator head adjusts quickly to apply tape in circular path or in a long straight line. Rear stabilizer adjusts right and left to allow for marking next to walls and pallet racks. Holds tape rolls with a 3" core and width between 1" minimum to 4½" maximum.

FLOOR TAPE APPLICATOR				
MODEL NUMBER	MAXIMUM ROLL DIAMETER	TAPE WIDTHS	WEIGHT (POUND)	
TPA-10 [Ⓢ]	6½"	1" - 4"	15	
TPA-20 [Ⓢ]	7"	1" - 4½"	21	
YELLOW/BLACK STRIPED FLOOR TAPE				
MODEL NUMBER	WIDTH	LENGTH	COLOR	WEIGHT (POUND)
YB-282-R [Ⓢ]	2"	82 FT.	YELLOW/BLACK	1
YB-382-R [Ⓢ]	3"	82 FT.	YELLOW/BLACK	1

Line Markers

Model LINE-SA - Lightweight applicator for marking paint lines on ground, trenches, construction and landscaping. Approximate stripe width is 1¼". Pull trigger to spray. Holds one standard inverted marking aerosol can of spray paint. Overall height is 37½". Steel construction with painted finish.

Model LINE-SA-W - Economical applicator - simply pull trigger to mark paint lines on floors. Holds one standard aerosol can of inverted marking spray paint. Wheels assist with creating an even line approximately 1¼" wide. Steel construction with painted finish.



model LINE-SA



model LINE-SA-W

MODEL NUMBER	DESCRIPTION	WEIGHT (POUND)
LINE-SA [Ⓢ]	HANDHELD WAND APPLICATOR	4
LINE-SA-W [Ⓢ]	PORTABLE APPLICATOR W/WHEELS	6

Reel Mover Handle

A reel mover handle is the perfect way to transfer wire reels throughout the workspace. The long handle allows the user to walk/stand in the proper upright position which diminishes the amount of time bending and twisting while moving reels manually. The strong construction gives the user the ability to secure the reel to the handle and transport throughout the designated working area. Works well in manufacturing and construction facilities.



model RMH-C-5020-3

MODEL NUMBER	DESCRIPTION	MAX REEL HEIGHT	MAX REEL LENGTH	MIN REEL CORE	MAX REEL CORE	WEIGHT (POUND)
RMH-C-5020-3	REEL MOVER	54"	20 ^{11/16"}	1 ^{11/16"}	3 ^{7/8"}	18

Welding Curtain Roll

Welding curtains promote safety throughout manufacturing and construction facilities. The strong flame retardant vinyl design keeps materials from passing into other work areas. The unit includes a pregrommeted top side for simply hanging in the designated work space. An assortment of colors are available.



model WCR-6025-G

48 Hours
to Ship

MODEL NUMBER	DESCRIPTION	TRANSPARENT COLOR	WEIGHT (POUND)
WCR-6025-G [Ⓢ]	WELDING CURTAIN ROLL 14 mil	GRAY	39
WCR-6025-O [Ⓢ]	WELDING CURTAIN ROLL 14 mil	ORANGE	39
WCR-6025-Y [Ⓢ]	WELDING CURTAIN ROLL 14 mil	YELLOW	39

Industrial Acrylic Convex Mirrors

These Acrylic Convex Mirrors eliminate those blind spots and danger areas found in most industrial settings. Lightweight design made from the finest quality materials, using Grade A Optical Acrylic. Comes standard with hanging or mounting hardware.

MODEL NUMBER	DESCRIPTION	OVERALL DIAMETER	DISTANCE COVERED	WEIGHT (POUND)
ROUND CONVEX MIRRORS				
CNVX-12 [®]	INDOOR USE	12"	12'	4
CNVX-18 [®]	INDOOR USE	18"	20'	5
CNVX-26 [®]	INDOOR USE	26"	26'	10
CNVX-30 [®]	INDOOR USE	30"	30'	12
CNVX-18-O [®]	OUTDOOR USE	18"	20'	10
CNVX-26-O [®]	OUTDOOR USE	26"	26'	16
CNVX-30-O [®]	OUTDOOR USE	30"	30'	20
CNVX-36-O [®]	OUTDOOR USE	36"	36'	28
CNVX-2618	RECTANGULAR	26"W x 18"H	26'	11
DOMES ACRYLIC MIRRORS				
DOME-18	360° FULL DOME	18"	18'	5
DOME-26	360° FULL DOME	28"	26'	9
DOME-32	360° FULL DOME	34"	32'	15
DOME-36	360° FULL DOME	36"	36'	18
DOME-H18	180° HALF DOME	18"	18'	3
DOME-H26	180° HALF DOME	28"	26'	5
DOME-H32	180° HALF DOME	34"	32'	10
OBLONG HALLWAY MIRROR				
OFF-EYE	OBLONG	16"W x 7¾"H	10' to 12'	3
WIDE VIEW CONVEX MIRRORS				
CNVX-W-16	INDOOR 4" DEEP	16"	16' to 20'	6
CNVX-W-24	INDOOR 5" DEEP	24"	25' to 30'	12
CNVX-W-32	INDOOR 7" DEEP	32"	35' to 40'	21
CNVX-WO-16	OUTDOOR 4" DEEP	16"	16' to 20'	8
CNVX-WO-24	OUTDOOR 5" DEEP	24"	25' to 30'	16
CNVX-WO-32	OUTDOOR 7" DEEP	32"	35' to 40'	24
INSPECTION MIRROR				
SIM-12-WF	WHEEL & LIGHT	12"	12'	12
SIM-8	INSPECTION MIRROR	8"	8'	7

48 Hours to Ship




model CNVX-2618



model CNVX-30-O



model DOME-H26



model DOME-26

1" OF DIAMETER
EQUALS 1 FOOT OF
VIEWING DISTANCE




WIDE VIEW CONVEX



STANDARD CONVEX



model CNVX-W-32



model SIM-12-WF



model SIM-8

Stainless Steel Flag Poles and American Flags

Flagpoles feature a bright-polished stainless steel finish to elegantly display your flag of choice. The one-piece stainless steel tapered construction will maintain its attractive finish for many years to come. Includes nylon rope, stainless steel rope cleat, and top pulley. Base plate is pre-drilled with four mounting holes. Flag poles are rated for 60 mph wind. United States flags are available in a

MODEL NUMBER	TOP DIAMETER	MIDDLE DIAMETER	BOTTOM DIAMETER	HEIGHT	RECOMMENDED FLAG SIZE (W x H)	WEIGHT (POUND)
FLP-20-SS [®]	3"	--	3½"	20'	5' x 3'	123
FLP-25-SS [®]	3"	3½"	4"	25'	6' x 4'	150
MODEL NUMBER	WIDTH (FEET)	HEIGHT (FEET)	USE WITH POLE MODEL	WEIGHT (POUND)		
AFL-20 [®]	5	3	20 FT. POLE	2		
AFL-25 [®]	6	4	25 FT. POLE	2		
AFL-30 [®]	8	5	30 FT. POLE	2		



48 Hours to Ship



FLAG SOLD SEPARATELY
Width of flag should not exceed
25% of the flag pole height.



model PT-MX-RT-46-BK



model PT-MX-3096-GN



model PT-PHX-3944-BKCD-ADA
Recycled Plastic Construction
ADA Compliant



model PT-PWT-2872-BKCD

Picnic Tables - Steel Mesh

Steel Mesh Picnic Tables are constructed of heavy-gauge steel mesh with thermoplastic coating on tabletops. The smooth, high gloss surface stays cool to the touch and resists fading, mold, and vandalism. The rugged tubular steel frame is powder coated black for rust prevention. Table corners are beveled for safety.

Prefix PT-MX-RT tables have an umbrella hole 1½"(ID).

MODEL NUMBER	COLOR	SIZE	WEIGHT (POUND)
ROUND PICNIC TABLES			
PT-MX-RT-46-BK	BLACK	46" DIAMETER	245
PT-MX-RT-46-BN	BROWN	46" DIAMETER	245
PT-MX-RT-46-GN	GREEN	46" DIAMETER	245
SQUARE PICNIC TABLES			
PT-MX-ST-46-BK	BLACK	46" x 46"	245
PT-MX-ST-46-BN	BROWN	46" x 46"	245
PT-MX-ST-46-GN	GREEN	46" x 46"	245
RECTANGLE PICNIC TABLES			
PT-MX-3072-BK	BLACK	72" LENGTH	216
PT-MX-3072-BN	BROWN	72" LENGTH	216
PT-MX-3072-GN	GREEN	72" LENGTH	216
PT-MX-3096-BK	BLACK	96" LENGTH	260
PT-MX-3096-BN	BROWN	96" LENGTH	260
PT-MX-3096-GN	GREEN	96" LENGTH	260

Picnic Tables & Benches - Recycled Plastic

Recycled Plastic Picnic Tables are constructed to provide many years of maintenance free service. Choose from multiple colors, sizes, and configurations. Molded in color resists fade and will not wear. ADA (wheelchair accessible) design also available. Suffix *BKCD* tables have a cedar color on the top/seats with black legs. Suffix *BKGY* tables have gray on the top/seats with black legs.

Prefix *PT-PHX* tables have an umbrella hole 1¾"(ID).

MODEL NUMBER	DESCRIPTION	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
PT-PHX-3944-BKCD	HEXAGON TABLE	69½" x 69½" x 30¼"	350
PT-PHX-3944-BKGY	HEXAGON TABLE	69½" x 69½" x 30¼"	350
PT-PHX-3944-BKCD-ADA	HEXAGON - ADA VERSION	69½" x 69½" x 30¼"	335
PT-PHX-3944-BKGY-ADA	HEXAGON - ADA VERSION	69½" x 69½" x 30¼"	335
PT-PWT-2872-BKCD	RECTANGLE WALK-THRU	72" x 58" x 29¾"	390
PT-PWT-2872-BKGY	RECTANGLE WALK-THRU	72" x 58" x 29¾"	390
PT-PWT-2896-BKCD	RECTANGLE WALK-THRU	96" x 58" x 29¾"	575
PT-PWT-2896-BKGY	RECTANGLE WALK-THRU	96" x 58" x 29¾"	575
PT-PAF-2872-BKCD	6' A-FRAME TABLE	72" x 60" x 30"	430
PT-PAF-2872-BKGY	6' A-FRAME TABLE	72" x 60" x 30"	430
PT-PAF-2896-BKCD	8' A-FRAME TABLE	96" x 60" x 30"	575
PT-PAF-2896-BKGY	8' A-FRAME TABLE	96" x 60" x 30"	575
PT-PAF-2896-BKCD-ADA	8' A-FRAME ADA VERSION	96" x 60" x 33½"	550
PT-PAF-2896-BKGY-ADA	8' A-FRAME ADA VERSION	96" x 60" x 33½"	550

Benches - Steel Mesh

Steel Mesh Benches are constructed of heavy-gauge steel mesh with thermoplastic coating. The smooth, high gloss surface stays cool to the touch and resists fading, mold, and vandalism. The rugged tubular steel frame is powder coated black for rust prevention. Bench corners are beveled for safety.



model BEN-MX-72-BN



MODEL NUMBER	COLOR	SIZE	WEIGHT (POUND)
BEN-MX-72-BK	BLACK	72" LENGTH	143
BEN-MX-72-BN	BROWN	72" LENGTH	143
BEN-MX-72-GN	GREEN	72" LENGTH	143
BEN-MX-96-BK	BLACK	96" LENGTH	160
BEN-MX-96-BN	BROWN	96" LENGTH	160
BEN-MX-96-GN	GREEN	96" LENGTH	160

Benches - Recycled Plastic

Recycled Plastic Benches are constructed to provide many years of maintenance free service. Molded in color resists fading and will not wear. Suffix *BKCD* benches have a cedar color on the seats with black legs. Suffix *BKGY* benches have gray on the seats with black legs.

MODEL NUMBER	DESCRIPTION	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
BEN-PDB1-48-BKCD	4' DELUXE BENCH	48" x 28" x 33¼"	165
BEN-PDB1-48-BKGY	4' DELUXE BENCH	48" x 28" x 33¼"	165
BEN-PDB1-72-BKCD	6' DELUXE BENCH	72" x 28" x 33¼"	260
BEN-PDB1-72-BKGY	6' DELUXE BENCH	72" x 28" x 33¼"	260



Park Benches - Recycled Plastic

Get the look of a traditional bench at an economic price. Made entirely of 100% post-consumer recycled plastic. Sustainability, quality, and comfort are combined in a maintenance free bench. It will never need scraping, staining, painting, or storage and stands up to the harshest weather Mother Nature can dish out. Permanent installation hardware and message engraving on back board is also available. Contact factory for details.

MODEL NUMBER	COLOR	OVERALL SIZE (W x L x H)	WEIGHT (POUND)
CAMBRIDGE BACKED BENCH WITH ARMS			
BEN-PCBA-48-BKBK	BLACK/BLACK	26¾" x 48" x 30¼"	79
BEN-PCBA-48-BKBN	BLACK/BROWN	26¾" x 48" x 30¼"	79
BEN-PCBA-48-BKCD	BLACK/CEDAR	26¾" x 48" x 30¼"	79
BEN-PCBA-48-BKCH	BLACK/CHARCOAL	26¾" x 48" x 30¼"	79
DELUXE BACKED BENCH			
BEN-PDB2-72-BKBK	BLACK/BLACK	26⅞" x 72" x 32½"	131
BEN-PDB2-72-BKBN	BLACK/BROWN	26⅞" x 72" x 32½"	131
BEN-PDB2-72-BKCD	BLACK/CEDAR	26⅞" x 72" x 32½"	131
BEN-PDB2-72-BKCH	BLACK/CHARCOAL	26⅞" x 72" x 32½"	131
ECON BACKED BENCH			
BEN-PECB-48-BKBK	BLACK/BLACK	26¼" x 48" x 32¼"	72
BEN-PECB-48-BKBN	BLACK/BROWN	26¼" x 48" x 32¼"	72
BEN-PECB-48-BKCD	BLACK/CEDAR	26¼" x 48" x 32¼"	72
BEN-PECB-48-BKCH	BLACK/CHARCOAL	26¼" x 48" x 32¼"	72
BEN-PECB-72-BKBK	BLACK/BLACK	26¼" x 72" x 32¼"	114
BEN-PECB-72-BKBN	BLACK/BROWN	26¼" x 72" x 32¼"	114
BEN-PECB-72-BKCD	BLACK/CEDAR	26¼" x 72" x 32¼"	114
BEN-PECB-72-BKCH	BLACK/CHARCOAL	26¼" x 72" x 32¼"	114
BEN-PECB-96-BKBK	BLACK/BLACK	26¼" x 96" x 32¼"	152
BEN-PECB-96-BKBN	BLACK/BROWN	26¼" x 96" x 32¼"	152
BEN-PECB-96-BKCD	BLACK/CEDAR	26¼" x 96" x 32¼"	152
BEN-PECB-96-BKCH	BLACK/CHARCOAL	26¼" x 96" x 32¼"	152
LANDMARK BACKED BENCH			
BEN-PLMB-96-BKBK	BLACK/BLACK	26¼" x 96" x 33⅜"	188
BEN-PLMB-96-BKBN	BLACK/BROWN	26¼" x 96" x 33⅜"	188
BEN-PLMB-96-BKCD	BLACK/CEDAR	26¼" x 96" x 33⅜"	188
BEN-PLMB-96-BKCH	BLACK/CHARCOAL	26¼" x 96" x 33⅜"	188
MONARQUE BACKED BENCH			
BEN-PMQB-72-BKBK	BLACK/BLACK	29" x 72" x 32⅜"	129
BEN-PMQB-72-BKBN	BLACK/BROWN	29" x 72" x 32⅜"	129
BEN-PMQB-72-BKCD	BLACK/CEDAR	29" x 72" x 32⅜"	129
BEN-PMQB-72-BKCH	BLACK/CHARCOAL	29" x 72" x 32⅜"	129
TRADITIONAL BACKED BENCH			
BEN-PTDB-72-BKBK	BLACK/BLACK	26¼" x 72" x 32½"	145
BEN-PTDB-72-BKBN	BLACK/BROWN	26¼" x 72" x 32½"	145
BEN-PTDB-72-BKCD	BLACK/CEDAR	26¼" x 72" x 32½"	145
BEN-PTDB-72-BKCH	BLACK/CHARCOAL	26¼" x 72" x 32½"	145
BEN-ABK	(4) "L" BRACKETS & (8) SCREWS	ground anchors not included	1





model TR-PSQ-22-BK-CD

Trash Receptacles

The Economy 22 gallon receptacles represent both value and quality in a space-saving design. Made in America of 100% post consumer recycled plastic, it is available in (3) three slat colors with a black top. It is not only a sustainable product, it can be used for trash or recyclable items with custom engraving available on the top, contact factory.

The large capacity 33 and 49 gallon receptacles can be used for trash or as part of a recycling station. Made in America of 100% post-consumer recycled plastic, includes an inner plastic liner and are available in (3) three colors with a black top. Stainless steel fasteners ensure a rust resistant, long life and are internal to provide a clean, blemish-free appearance. Keep your environment clean and keep plastic out of the landfill at the same time.

We've added flare to utility with our Round Flare Top Receptacle! The unique design has an inner liner and 33 gallon capacity. Made in America of 100% post-consumer recycled plastic. It's eco-friendly while helping keep trash/recyclables in their place.



model TR-PRRC-33-CH



model TR-PRF-33-CD



model TR-PR-49-CH

MODEL NUMBER	CAPACITY (GALLONS)	OVERALL SIZE (W x L x H)	COLOR	WEIGHT (POUND)
22 GALLON ECONOMY RECEPTACLE				
TR-PSQ-22-BK-BK	22	17" x 18½" x 28"	BLACK/BLACK	70
TR-PSQ-22-BK-CD	22	17" x 18½" x 28"	BLACK/CEDAR	70
TR-PSQ-22-BK-CH	22	17" x 18½" x 28"	BLACK/CHARCOAL	70
33 GALLON ROUND RECEPTACLE				
TR-PR-33-BK	33	26 ³ / ₁₆ " x 30"	BLACK	132
TR-PR-33-BN	33	26 ³ / ₁₆ " x 30"	BROWN	132
TR-PR-33-CD	33	26 ³ / ₁₆ " x 30"	CEDAR	132
TR-PR-33-GN	33	26 ³ / ₁₆ " x 30"	GREEN	132
TR-PR-33-CH	33	26 ³ / ₁₆ " x 30"	CHARCOAL	132
TR-PR-33-SD	33	26 ³ / ₁₆ " x 30"	SAND	132
33 GALLON ROUND RECEPTACLE WITH RAINCAP				
TR-PRRC-33-BK	33	26 ³ / ₁₆ " x 37"	BLACK	146
TR-PRRC-33-BN	33	26 ³ / ₁₆ " x 37"	BROWN	146
TR-PRRC-33-CD	33	26 ³ / ₁₆ " x 37"	CEDAR	146
TR-PRRC-33-GN	33	26 ³ / ₁₆ " x 37"	GREEN	146
TR-PRRC-33-CH	33	26 ³ / ₁₆ " x 37"	CHARCOAL	146
TR-PRRC-33-SD	33	26 ³ / ₁₆ " x 37"	SAND	146
33 GALLON FLARED TOP RECEPTACLE				
TR-PRF-33-CD	33	30" x 33 ⁹ / ₁₆ "	CEDAR	160
49 GALLON ROUND RECEPTACLE				
TR-PR-49-BK	49	29 ⁹ / ₁₆ " x 34½"	BLACK	161
TR-PR-49-BN	49	29 ⁹ / ₁₆ " x 34½"	BROWN	161
TR-PR-49-CD	49	29 ⁹ / ₁₆ " x 34½"	CEDAR	161
TR-PR-49-GN	49	29 ⁹ / ₁₆ " x 34½"	GREEN	161
TR-PR-49-CH	49	29 ⁹ / ₁₆ " x 34½"	CHARCOAL	161
TR-PR-49-SD	49	29 ⁹ / ₁₆ " x 34½"	SAND	161
49 GALLON ROUND RECEPTACLE WITH RAINCAP				
TR-PRRC-49-BK	49	29 ⁹ / ₁₆ " x 42½"	BLACK	171
TR-PRRC-49-BN	49	29 ⁹ / ₁₆ " x 42½"	BROWN	171
TR-PRRC-49-CD	49	29 ⁹ / ₁₆ " x 42½"	CEDAR	171
TR-PRRC-49-GN	49	29 ⁹ / ₁₆ " x 42½"	GREEN	171
TR-PRRC-49-CH	49	29 ⁹ / ₁₆ " x 42½"	CHARCOAL	171
TR-PRRC-49-SD	49	29 ⁹ / ₁₆ " x 42½"	SAND	171
HARDWARE				
TR-ABK	(4) "L" BRACKETS & (8) SCREWS ground anchors not included			1

Expanded Metal Trash Can

The expanded metal trash cans are perfect for a variety of settings. The mesh style metal design allows for the amount level to be determined easier and allow for an easier cleanup. The strong, yet lightweight, construction withstands adverse conditions on a consistent basis and be moved easily without the need of extra personnel when empty. Available in a variation of colors.

MODEL NUMBER	CAPACITY (GALLONS)	OVERALL SIZE (W x L x H)	COLOR	WEIGHT (POUND)
48 GALLON RECEPTACLE				
TR-MXR-48-BK [®]	48	23½" x 23½" x 32¾"	BLACK	35
TR-MXR-48-HDG [®]	48	23½" x 23½" x 32¾"	GALVANIZED	35
TR-MXR-48-GN [®]	48	23½" x 23½" x 32¾"	GREEN	35
TR-MXR-48-RD [®]	48	23½" x 23½" x 32¾"	RED	35



48 Hours
to Ship

CA Residents see
WARNING A, Pg. 459


Tree Grates

Tree Grates are the perfect addition to any facilities landscaping resources. The grate provides safety to the vegetation while maintaining the quality of the surrounding environment. The units are available in both square and round shapes to better fit the users landscaping needs. With a lightweight design, the units are able to be easily installed without the use of additional personnel. As the tree grows, the inside grate diameter can be expanded for a better fit. For best use, place each half of the grate around the tree on a flat surface and lock in place with the included hardware. ADA compliant.


Tree Grate frames delivers great support to any existing or new grates. For best use, place each portion of the frame under the surface edge and fasten into place. Once in place, a new or existing grate can be fitted inside the frame for a smooth, uninterrupted surface.

Frame comes complete with four (4) 1 ½" square pre-drilled plastic frames (42" length for use with 48" square grate or 54" length for use with 60" square grate).

MODEL NUMBER	DESCRIPTION	OVERALL SIZE (W x L x H)	COLOR	WEIGHT (POUND)
TREE GRATES				
TG-3R-BK	3 FT. ROUND	36" x 36" x 2"	BLACK	23
TG-4S-BK	4 FT. SQUARE	48" x 48" x 2"	BLACK	43
TG-5S-BK	5 FT. SQUARE	60" x 60" x 2"	BLACK	65
FRAMES				
TG-4S-F-BK	4 FT. SQUARE FRAME	1½" x 42" x 1½"	BLACK	20
TG-5S-F-BK	5 FT. SQUARE FRAME	1½" x 54" x 1½"	BLACK	20



model TG-3R-BK



model TG-4S-BK



Salt Boxes

A salt box is a great addition to any business or public facility. The box is constructed of a durable polyethylene that withstands the harsh effects of salt and other ice melting products. The bright color with lid provides great visibility in the work area during times of need. The unit is lockable for both safe transporting and to ensure the only users are authorized personnel. The large capacity allows for great amounts of material to be placed in the box for space saving efficiency.

The heavy duty scoop is perfect for the business or at home when handling salt and other winter related snow melting material. The polyethylene construction is both lightweight and durable for continuous use during the harsh winter months. The unit is brightly colored for simple visibility and quick locating during times of use.

MODEL NUMBER	DESCRIPTION	OVERALL SIZE (W x L x H)	VOLUME CUBIC FEET	WEIGHT (POUND)
ESB-5	ECONOMY	31½" x 22" x 24"	5	21
ESB-10	ECONOMY	41½" x 27" x 30½"	10	35
HDSB-5.5	HEAVY DUTY	32" x 22" x 24"	5 ½	10
HDSB-11	HEAVY DUTY	42" x 28" x 31"	11	50
HDSB-18	HEAVY DUTY	35" x 49" x 35"	18	65
SSP-05	SALT SCOOPS - 12 PER BOX			3



model ESB-10



model SSP-05



model HDSB-11



Tilt Trucks

Durable plastic construction withstands extreme summer heat and allows collecting waste from multiple bins at a collective time. Great for high traffic areas such as: warehouses, fairs, ball parks, schools, etc. Strong, one-piece molded polyethylene body with steel base tip support and a balanced design to allow for simple dumping by one person. Easily portable on 2 large rubber wheels and two swivel wheels. Tapered front makes it easier to pour materials into yet another larger container. Rust resistant powder coated frame for strength and durability. Keep your waste out of sight in our medium duty and easy-to-move tilt trucks. Not for use with fork trucks.



MODEL NUMBER	VOLUME CUBIC YARDS	UNIFORM CAPACITY	OVERALL SIZE (W x L x H)	WEIGHT (POUND)
TDT-50-LD-BLACK	1/2	450 lb.	28" x 62" x 35"	91
TDT-50-LD-BLUE	1/2	450 lb.	28" x 62" x 35"	91
TDT-50-LD-RED	1/2	450 lb.	28" x 62" x 35"	91
TDT-50-LD-YELLOW	1/2	450 lb.	28" x 62" x 35"	91
TDT-50-MD-BLACK	1/2	850 lb.	28" x 62" x 35"	108
TDT-50-MD-BLUE	1/2	850 lb.	28" x 62" x 35"	108
TDT-50-MD-RED	1/2	850 lb.	28" x 62" x 35"	108
TDT-50-MD-YELLOW	1/2	850 lb.	28" x 62" x 35"	108
TDT-50-HD-BLACK	1/2	1,400 lb.	28" x 62" x 35"	113
TDT-50-HD-BLUE	1/2	1,400 lb.	28" x 62" x 35"	113
TDT-50-HD-RED	1/2	1,400 lb.	28" x 62" x 35"	113
TDT-50-HD-YELLOW	1/2	1,400 lb.	28" x 62" x 35"	113
TDT-100-LD-BLACK	1	850 lb.	32" x 73" x 42"	113
TDT-100-LD-BLUE	1	850 lb.	32" x 73" x 42"	113
TDT-100-LD-RED	1	850 lb.	32" x 73" x 42"	113
TDT-100-LD-YELLOW	1	850 lb.	32" x 73" x 42"	113
TDT-100-MD-BLACK	1	1,250 lb.	32" x 73" x 43"	135
TDT-100-MD-BLUE	1	1,250 lb.	32" x 73" x 43"	135
TDT-100-MD-RED	1	1,250 lb.	32" x 73" x 43"	135
TDT-100-MD-YELLOW	1	1,250 lb.	32" x 73" x 43"	135
TDT-100-HD-BLACK	1	2,100 lb.	32" x 73" x 43"	140
TDT-100-HD-BLUE	1	2,100 lb.	32" x 73" x 43"	140
TDT-100-HD-RED	1	2,100 lb.	32" x 73" x 43"	140
TDT-100-HD-YELLOW	1	2,100 lb.	32" x 73" x 43"	140



Skid Steer Buckets

Skid steer buckets provide an easy way to transfer products, both big and small. The universal mounting system allows the unit to be utilized in conjunction with a variety of skid steers on the market. A high strength front cutting edge resists wear and cuts through the toughest of terrain. With a reinforced bottom plate and sides, and an all welded steel construction, this bucket will perform at the highest levels. The back plate is designed to move liquid materials like concrete. An anti-slip step guard is functionally placed at the top edge of the bucket for safe exiting of the skid steer. Excellent for landscaping, farming, and residential operations.

Good for handling lightweight materials such as: *dirt, mulch, snow, and sand.*

MODEL NUMBER	OVERALL SIZE (W x D x H)	HEAPED CAPACITY	WEIGHT (POUND)
EA-SKSB-60-LP	60" x 31 ¹⁵ / ₁₆ " x 18 ¹ / ₈ "	13 cu. ft.	321
EA-SKSB-66-LP	66" x 31 ¹⁵ / ₁₆ " x 18 ¹ / ₈ "	15 cu. ft.	336
EA-SKSB-68-LP	68" x 31 ¹⁵ / ₁₆ " x 18 ¹ / ₈ "	16 cu. ft.	351
EA-SKSB-72-LP	72" x 31 ¹⁵ / ₁₆ " x 18 ¹ / ₈ "	17 cu. ft.	366
EA-SKSB-76-LP	76" x 31 ¹⁵ / ₁₆ " x 18 ¹ / ₈ "	18 cu. ft.	376



Industrial Scooter

Get where you need to be quickly and safely with our manually powered Industrial Scooter. Sturdy foot rest includes a manually operated rear brake that safely stops the Scooter at your destination. Fixed height handle bars control front wheel maneuvering through narrow aisles and doorways. A 25" wide x 21" long front platform holds up to 100 uniform pounds, ideal for crates, boxes, and other small loads. Rolls on high performance smooth rolling 8" x 1¹/₄" polyurethane wheels. Ships knocked down.

MODEL NUMBER	OVERALL SIZE (W x L x H)	PLATFORM SIZE (W x L)	RIDER CAPACITY	WEIGHT (POUND)
SCOOT-DLX	27" x 61" x 40"	25" x 21"	230 lb.	72



Industrial Bicycles

A quick, easy, and safe way to move around large facilities. Built with rider friendly features and the ability to handle various loads while moving through a facility with ease and efficiency. A three wheel design includes hand brakes for sure stopping. Adjustable height seat for different sized people. Large payload / cargo area included.

MODEL NUMBER	OVERALL SIZE (W x L x H)	UNIFORM STATIC CAPACITY	COLORS	WEIGHT (POUND)
IBIKE-3-DC-R	29" x 70" x 43"	250 lb.	RED	72
IBIKE-3-DC-B	29" x 70" x 43"	250 lb.	BLUE	72
IBIKE-3-DC-G	29" x 70" x 43"	250 lb.	GREEN	72
IBIKE-3-DC-P	29" x 70" x 43"	250 lb.	PURPLE	72
IBIKE-3-HH-Y	33½" x 79" x 45"	500 lb.	YELLOW	146
IBIKE-3-HH-BL	33½" x 79" x 45"	500 lb.	BLACK	146
IBIKE-3-DCHH-Y	29" x 70" x 43"	350 lb.	YELLOW	113
OPTIONAL REAR BASKET (WORKS WITH IBIKE-3-DCHH-Y)				
IBIKE-3-DCHH-RWB	21" x 9" x 15"	60	WHITE	7



model
IBIKE-3-HH-BL

model
IBIKE-3-DCHH-Y

Eco-Friendly Bicycle Racks

Eco-Friendly Bike Racks provide users with a high level of security to lock up their bikes and other recreational toys. Made in America of 100% post-consumer recycled plastic, the six posts fit perfectly where space is limited. Promote a healthy lifestyle in your school, community, and public spaces by providing a secure rack to park bikes.

MODEL NUMBER	INSERT POSITIONS	OVERALL SIZE (W x L x H)	COLORS	WEIGHT (POUND)
BR-P6-BK-BK	6	42" x 48 ⁷ / ₁₆ " x 31"	BLACK/BLACK	125
BR-P6-BK-CD	6	42" x 48 ⁷ / ₁₆ " x 31"	BLACK/CEDAR	125
BR-P6-BK-CH	6	42" x 48 ⁷ / ₁₆ " x 31"	BLACK/CHARCOAL	125
BR-P10-BK-BK	10	42" x 72" x 31"	BLACK/BLACK	187
BR-P10-BK-CD	10	42" x 72" x 31"	BLACK/CEDAR	187
BR-P10-BK-CH	10	42" x 72" x 31"	BLACK/CHARCOAL	187
BR-ABK	(4) "L" BRACKETS & (8) SCREWS ground anchors not included			1



model
BR-P10-BK-CH




model
BR-P10-BK-CD

Bicycle Racks

Our Bicycle Racks make it easy to store bikes where space is at a premium. Welded steel units feature eight (8) mounting flanges with pre-drilled 7/16" holes for easy mounting with the exception of model numbers BR-GL-BK and BR-GL-G which has two (2) ¾" mounting holes. Hardware is sold separately. Racks are shipped fully-assembled and ready to use. Available in a powder coat black or galvanized finish. Other powder coat finishes are available. Please contact factory.

MODEL NUMBER	BIKE CAPACITY	MOUNTING STYLE	OVERALL SIZE (W x L x H)	WEIGHT (POUND)
BLACK POWDER COAT FINISH				
BR-L2-BK	5	GROUND	4" x 31" x 36"	25
BR-L3-BK	7	GROUND	4" x 49" x 36"	36
BR-ST-BK	2	GROUND	20" x 38 ⁵ / ₁₆ " x 26 ¹ / ₂ "	31
BR-M3S-BK	3	GROUND	13 ¹³ / ₁₆ " x 45 ⁷ / ₈ " x 14 ⁹ / ₁₆ "	31
BR-M3D-BK	6	GROUND	27 ¹ / ₄ " x 42" x 14 ⁹ / ₁₆ "	53
BR-M3S-W-BK	3	WALL	12 ⁷ / ₈ " x 40 ³ / ₈ " x 4 ¹ / ₁₆ "	23
BR-GL-BK	4	GROUND	5 ⁵ / ₁₆ " x 12 ³ / ₄ " x 22 ¹ / ₂ "	22
GALVANIZED FINISH				
BR-L2-GAL	5	GROUND	4" x 31" x 36"	25
BR-L3-GAL	7	GROUND	4" x 49" x 36"	36
BR-ST-GAL	2	GROUND	20" x 38 ⁵ / ₁₆ " x 26 ¹ / ₂ "	31
BR-M3S-GAL	3	GROUND	13 ¹³ / ₁₆ " x 45 ⁷ / ₈ " x 14 ⁹ / ₁₆ "	31
BR-M3D-GAL	6	GROUND	27 ³ / ₁₆ " x 42" x 14 ⁹ / ₁₆ "	53
BR-M3S-W-GAL	3	WALL	12 ⁷ / ₈ " x 40 ³ / ₈ " x 4 ¹ / ₁₆ "	23
BR-GL-G	4	GROUND	5 ⁵ / ₁₆ " x 12 ³ / ₄ " x 22 ¹ / ₂ "	22
AS-383	3/8" x 3"L CONCRETE ANCHOR (Sold Each) for 7/16" holes			1
AS-584	5/8" x 4"L CONCRETE ANCHOR (Sold Each) for 3/4" holes			1



model BR-L3-BK



model BR-L2-BK



model BR-ST-BK



model BR-M3S-BK



model BR-M3D-BK


SPECIAL POWDER COAT FINISH OPTIONS			
ERGO BLUE	SODA RED		
SKY BLUE	BUBBLE GUM		
SILVER LINING	CITRUS ORANGE		
MACHINE GRAY	YELLOW		
BATTLESHIP GRAY	HUNTER GREEN		
BROWN	TRACTOR GREEN		
KHAKI TAN	SNOWY WHITE		
SANDY BEIGE	LIQUID ENAMEL PRIMER		



model BR-GL-G



model BR-M3S-W-BK





48 Hours
to Ship

TYPE A



TYPE B



Deluxe Spring Driven Low Pressure Hose Reels

Keep air hoses off the floor and out of the way. Minimize labor, save storage space, protect against trip hazards and damaged hoses. For use with air and water only. Solid steel construction with heavy-duty brackets to resist hose pull. All reels have a full shaft and swivel to assure maximum product delivery. Maximum temperature is 150° F. Maximum pressure is 300 psi / 21 bar. Includes self retracting hose.

TYPE	MODEL NUMBER	OVERALL SIZE (W x D x H)	INSIDE HOSE DIAMETER	LENGTH OF HOSE	WEIGHT (POUND)
A	VHR-20-44	6¼" x 15" x 15"	1/4"	20 FOOT	19
A	VHR-35-44	5½" x 12½" x 13"	1/4"	35 FOOT	31
A	VHR-17-46	6" x 15" x 15½"	3/8"	17 FOOT	31
A	VHR-25-46	6½" x 14¾" x 15½"	3/8"	25 FOOT	26
A	VHR-50-56	7½" x 19½" x 20"	3/8"	50 FOOT	43
B	VHR-35-58	8" x 9¼" x 18"	1/2"	35 FOOT	43
B	VHR-50-78	8¼" x 21" x 19¾"	1/2"	50 FOOT	55

48 Hours
to Ship



model
SHR-P-38-50

Standard Spring Driven Low Pressure Hose Reels

Keep air hoses off the floor and out of the way. Minimize labor, save storage space, protect against trip hazards and damaged hoses. Maximum pressure is 300 psi / 20 bar. Includes self retracting hose.

Model SHR-P-38-50 is constructed of durable, high quality impact resistant polypropylene. A positive latching mechanism automatically locks hose at a desired length. A safety lock prevents the hose from moving in either direction. An integral wall/overhead swivel bracket and 36" lead hose are included. Maximum temperature is 140° F.

MODEL NUMBER	DESCRIPTION	OVERALL SIZE (W x D x H)	INSIDE HOSE DIAMETER	LENGTH OF HOSE	WEIGHT (POUND)
SHR-P-38-50	PLASTIC	8¾" x 17½" x 17¼"	3/8"	50 FOOT	23

48 Hours
to Ship



model
REEL-16L



Air Hose Reel

Help eliminate twists and tangles of hoses, save storage space, protect against trip hazards and damaged hoses with Air Hose Reels. This arm style reel is constructed of all steel. Quick and simple manual hand crank and spring loaded axle helps reel in up to 100 feet of 3/8" hose or 50 feet of 1/2" hose. Valve assembly is rated at 100 psi and 25 cfm. Unit can be mounted both vertically or horizontally. The wall bracket measures 7"W x 3"H. Hose is not included.

MODEL NUMBER	DESCRIPTION	OVERALL SIZE (W x D x H)	USABLE SPACE	WEIGHT (POUND)
REEL-16L	ARM STYLE	14" x 17¾" x 18"	5"	14

Electric Cord Reels 115V 1-PHASE STANDARD

Help eliminate the danger of tangled electrical cords with these Electric Cord Reels. The compact design is spring retractable and engineered for industrial use. Complete with 4 foot pigtail and three prong plug, 115V, 60 Hz single phase. Ideal for indoor non-weather tight applications only. UL listed and CSA certified.

Model ECR-45-S comes with a 15 AMP 3 wire single receptacle with clamp type strain relief.

Model ECR-45-D features a duplex outlet box and ground fault circuit interrupter.

Comes with a 20 AMP 3 wire double receptacle.

Model ECR-50 has an incandescent lamp and single receptacle. Head has tool tap, push through winch and metal grounded guard. 75 watt bulb maximum. Bulb not included.



model
ECR-45-S



model
ECR-45-D



model
ECR-50

MODEL NUMBER	DESCRIPTION	CORD LENGTH	WIRE GAUGE	WEIGHT (POUND)
ECR-45-S	SINGLE RECEPTACLE	45 FEET	12	24
ECR-45-D	DOUBLE RECEPTACLE	45 FEET	12	31
ECR-50	LAMP WITH RECEPTACLE	50 FEET	16	25

Retractable Cord Reels with Work Lights

A retractable cord reel is the perfect accessory for maintenance areas and general workshops. Retractable cord with spring drive work light included for quick visibility while the steel design shows its strength throughout adverse conditions and surroundings. The unit can be simply mounted for permanent use in the desired location. The included fluorescent light is great for hanging in work areas and using in those hard to reach spots. Available in cord lengths of 35 and 50 feet.

MODEL NUMBER	DESCRIPTION	CORD LENGTH	CORD GAUGE	WEIGHT (POUND)
FWLCR-20-18	FLUORESCENT 13 WATT	35 FEET	18	23
FWLCR-25-18	FLUORESCENT 15 WATT	50 FEET	18	24



model FWLCR-20-18

Tool Balancers

Tool Balancers are the economical choice for balancing tools. The strong, durable construction has a smooth finish with an unyielding ergonomic convenience. Large cable opening for simple connectivity to units minimizes set up and completion times. An adjustable cable with hand winding ability works great for finding a precise tension point and positioning during use. Spring operation - no electricity needed.

MODEL NUMBER	CABLE LENGTH (FEET)	MINIMUM UNIFORM LOAD	MAXIMUM UNIFORM LOAD	WEIGHT (POUND)
TBR-1 Ⓢ	6	0 lb.	1.5 lb.	2
TBR-3 Ⓢ	6	1½ lb.	3 lb.	2
TBR-5 Ⓢ	6	3 lb.	5 lb.	2
TBR-10 Ⓢ	8	5 lb.	10 lb.	7
TBR-12 Ⓢ	8	8 lb.	12 lb.	10
TBR-15 Ⓢ	8	10 lb.	15 lb.	10
TBR-23 Ⓢ	8	16 lb.	23 lb.	10

48 Hours
to Ship




model TBR-5

Warning Sirens

An ideal method to warn people of dangerous situations including: severe weather warnings, emergency circumstances, terror situations, military alerts, and correctional facility alerts. Easy hand crank operation. Type A-E include a convenient carrying bag. Type F-J are easy to install through your local contractors or electricians.

TYPE	MODEL NUMBER	AUDIBLE DISTANCE	STONE	CONSTRUCTION	WEIGHT (POUND)
A	SIREN-100-P-C Ⓢ	1/4 MILE	SINGLE	PLASTIC	2
B	SIREN-100-P-GN Ⓢ	1/4 MILE	SINGLE	PLASTIC	2
C	SIREN-100-C Ⓢ	1/4 MILE	SINGLE	STEEL	4
D	SIREN-100-S Ⓢ	1/4 MILE	SINGLE	STEEL	4
E	SIREN-100-GN Ⓢ	1/4 MILE	SINGLE	STEEL	2
F	SIREN-100-BM Ⓢ	1/4 MILE	SINGLE	STEEL	4
G	SIREN-100-TP Ⓢ	1/4 MILE	SINGLE	STEEL	4
H	SIREN-120 Ⓢ	1/2 MILE	SINGLE	STEEL	22
I	SIREN-SV Ⓢ	1/4 MILE	SINGLE	STEEL	6
J	SIREN-SV-AR Ⓢ	1/4 MILE	SINGLE	STEEL/RED	7

48 Hours
to Ship



Specialty Wheelbarrows

Ideal for use in both commercial or agricultural settings. Exceptional for use in "green" construction zones and/or maintenance zones. Will not puncture or sink into surfaces that otherwise might be susceptible by metal leg-brace supports. Weight is distributed via 4 wheels, which create a balanced movement of load.

Optional Ergonomic Handles, model WLB-HDL, reduces wrist torque while you manage heavy loads. The patented pivot-point allows the user to carry and lift loads with greater control reducing strain on the wrists, elbows, and lower back. Durable nylon construction.

MODEL NUMBER	CUBIC FEET	WHEEL TYPE	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
WLB4-300	6	PNEUMATIC	26" x 59" x 29½"	85
WLB4-400	8	PNEUMATIC	32" x 60" x 31½"	90
WLB4-500	10	PNEUMATIC	35" x 60" x 34"	94
WLB-HDL		ERGONOMIC HANDLES		12



model WLB4-300



model WLB4-400



model
STOR-96-G-W-1RH

Storage Buildings

Modular Storage Buildings are ideal for keeping valuable items secure. Constructed of maintenance free galvanized corrugated paneling. The door measures 45"W x 74"H usable and features a right-side hinged lock (padlock not included). Modular design is easy to assemble. Once assembled, unit can be moved with a fork lift. Each unit features a wooden floor 5¾" high to help keep products dry. Built-in rain gutters for water drainage is standard.



CA Residents see
WARNING A, Pg. 459

model
STOR-912-G-W-1RH

MODEL NUMBER	OVERALL SIZE (W x D x H)	USABLE SIZE (W x D x H)	WEIGHT (POUND)
STOR-96-G-W-1RH	109 ³ / ₁₆ " x 76 ¹ / ₂ " x 84 ³ / ₄ "	104 ³ / ₄ " x 69 ³ / ₄ " x 77 ⁷ / ₁₆ "	1010
STOR-912-G-W-1RH	109 ¹ / ₂ " x 152 ¹³ / ₁₆ " x 84 ¹³ / ₁₆ "	104 ³ / ₄ " x 145 ³ / ₄ " x 77 ⁷ / ₁₆ "	1785




model
SHED-5932

Utility Steel Storage Sheds

The Utility Steel Storage Sheds are used for holding all kinds of materials or tools. The hinged door provides access to the shed and the slanted roof helps with rain run-off. The shed has an open floor design (floor is not included) and a lockable door latch (padlock not included). Unit has a zinc-plated finish that prevents rust. The easy to assemble design ships knock-down with installation instructions and hardware included. Side door design for use in long narrow spaces.

MODEL NUMBER	SIDE OF BUILDING THE DOOR OPENS	OVERALL SIZE (W x D x H)	USABLE SIZE (W x H)	WEIGHT (POUND)
SHED-5932	SIDE	60" x 33 ³ / ₄ " x 79 ¹ / ₂ "	57" x 75"	128



model MDS-96-DR
72"W x 83"H &
36"W x 83"H DOORS

Multi-Duty Storage Buildings

Constructed of heavy duty steel these Multi-Duty Storage Buildings stand up in multiple weather conditions; rain, sleet, and snow. The 18 gauge steel roof is contoured for water drainage and will hold snow up to 45 lbs./sq-foot. The sides are constructed of 28 gauge steel siding. Usable size 109¼"W x 75¼"D x 80"H. Lag down plates are included for securing unit to the concrete. Ships knocked down, assembly required.

MODEL NUMBER	DESCRIPTION	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
MDS-96-DR	SHELTER WITH DOORS	120" x 95 ¹ / ₂ " x 90 ¹ / ₁₆ "	1080
MDS-96-SM	SMOKERS SHELTER	120" x 95 ¹ / ₂ " x 90 ¹ / ₁₆ "	1000
MDS-96-BK	BICYCLE STORAGE SHELTER	120" x 95 ¹ / ₂ " x 90 ¹ / ₁₆ "	927
AS-125 [®]	ANCHOR BOLTS FOR CONCRETE (1) 1/2" x 5"		1
AS-125-4PK [®]	ANCHOR BOLTS FOR CONCRETE (4) 1/2" x 5"		4



model
MDS-96-SM



model MDS-96-BK
INCLUDES STEEL
BICYCLE RACK

Smoking Shelter / Bus Stop

Shelters feature rugged welded steel construction for strength and durability. Side panels are constructed of semi-clear polycarbonate. The top is made from corrugated polycarbonate sheet with a silver baked-in powder coated toughness. Mounting plates included. Heating options available for those cold weather applications, contact factory. Ships knocked down, assembly required.



48 Hours
to Ship



model SSH-7939-80

MODEL NUMBER	USABLE SIZE (W x D x H)	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
SSH-7939-80	69 $\frac{3}{4}$ " x 37 $\frac{1}{2}$ " x 77 $\frac{3}{16}$ "	76 $\frac{1}{4}$ " x 49 $\frac{5}{16}$ " x 83 $\frac{9}{16}$ "	270
AS-383	ANCHOR BOLTS FOR CONCRETE (1) 3/8" x 3"		1
AS-383-4PK	ANCHOR BOLTS FOR CONCRETE (4) 3/8" x 3"		4

LunarGlo LED Light - Option for storage sheds and shelters

An American made solar light unit that has the ability to provide up to 80 hours of light on a single charge. Designed to function even in the toughest of weather conditions. Provides light to insure the safety of people taking a smoke break or waiting for a taxi or mass transit. Easy to install light has no moving parts and is powered by the sun. Includes (4) four ultra bright LED bulbs and a lithium ion battery.



New



model LGL-LED

MODEL NUMBER	DESCRIPTION	OVERALL SIZE (W x L x H)	BULB TYPE	WEIGHT (POUND)
LGL-LED	ROOF LIGHT	5 $\frac{5}{8}$ " x 5 $\frac{5}{8}$ " x 3 $\frac{1}{8}$ "	L ED	2

Aluminum Smokers Bollards

Manufactured from aluminum alloy for an attractive finish. Includes internal storage container for holding cigarettes. Easy to empty design. Floor-mounted unit includes (4) pre-drilled mounting holes. Wall mounted unit includes hardware.

MODEL NUMBER	DESCRIPTION	HEIGHT	OUTSIDE DIAMETER	WEIGHT (POUND)
SMK-F-35A	FLOOR MOUNTED	35"	3 $\frac{1}{4}$ "	13
SMK-W-19A	WALL MOUNTED	19"	3 $\frac{1}{4}$ "	4
AS-124-4PK	ANCHOR BOLTS FOR CONCRETE (4) 1/2" x 4"			4

48 Hours
to Ship



model SMK-F-35A



model SMK-W-19A

Driver Cages

Driver Cages are an application that is placed around an entrance in a warehouse. This is used to keep truck drivers, and delivery personnel secluded in one place when entering the warehouse or making a delivery. Each driver cage includes a key lock on the driver side (48" side), a push bar on the warehouse side, and a 2' x 1' 8" slide up service window with shelf. Driver Cage prevents people from wandering throughout the warehouse, getting lost or hurt in the warehouse, as well as additional security. Cages consists of rectangular 2" x 1" mesh, 10 gauge woven wire, and a wet enamel gray finish. Optional colors available, contact factory.

MODEL NUMBER	USABLE SIZE (W x D)	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
2 SIDED DRIVER CAGE			
WPC-D-4X4-2	48" x 48"	52" x 54" x 101 $\frac{1}{4}$ "	521
WPC-D-4X6-2	72" x 48"	78" x 54" x 101 $\frac{1}{4}$ "	576
WPC-D-4X8-2	96" x 48"	102" x 54" x 101 $\frac{1}{4}$ "	598
3 SIDED DRIVER CAGE			
WPC-D-4X4-3	48" x 48"	52" x 54" x 101 $\frac{1}{4}$ "	595
WPC-D-4X6-3	72" x 48"	78" x 54" x 101 $\frac{1}{4}$ "	639
WPC-D-4X8-3	96" x 48"	102" x 54" x 101 $\frac{1}{4}$ "	677



model WPC-D-4X6-3



model WPC-10X10-4C

Wire Cages

Modular systems offer security, storage, and safety for many applications. Stackable panel design allows for easy installation and results in a clean finish, putting this system above the rest. Using wire partitions can save in inventory costs, are more economical alternatives to modular offices and drywall, and can increase safety - all benefits to your business. Constructed of 2" x 2" mesh, 10 gauge welded wire with a powder coat gray finish.

MODEL NUMBER	DESCRIPTION	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
HINGED DOOR TYPE			
WPC-8X8-3NC	3 SIDED, NO CEILING	102" x 100" x 101 1/4"	569
WPC-8X8-4NC	4 SIDED, NO CEILING	100" x 100" x 101 1/4"	671
WPC-8X8-4C	4 SIDED, W/ CEILING	100" x 100" x 101 1/4"	773
WPC-12X12-4NC	4 SIDED, NO CEILING	150" x 150" x 101 1/4"	854
SLIDING DOOR TYPE			
WPC-10X10-3NC	3 SIDED, NO CEILING	124" x 124" x 125 1/4"	759
WPC-10X10-4NC	4 SIDED, NO CEILING	124" x 124" x 125 1/4"	867
WPC-10X10-4C	4 SIDED, W/ CEILING	124" x 124" x 125 1/4"	1001



model SHOP-DO



model SHOP-DW



Shop Desks

Ideal for supervisors, shipping and receiving, or anyone who works on their feet. Sloped top for ergonomic comfort while standing and working. Features roomy writing surface and storage area. Legs are adjustable in 1/2" increments. Cabinet unit comes with built-in lockable doors and all units come with a lockable drawer. Drawer size is 24"W x 28"D x 3 1/2"H. Units ship knockdown for freight savings.

model SHOP-DC



48 Hours to Ship

MODEL NUMBER	DESCRIPTION	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
SHOP-DO	OPEN SHOP DESK	36 7/8" x 29 15/16" x 54 3/4"	120
SHOP-DC	CABINET SHOP DESK	35 1/2" x 33 3/4" x 49"	167
SHOP-DW	WALL MOUNTED DESK	36 3/4" x 30" x 19 1/2"	92

Storage Lockers

Whether you need this fully welded storage locker for small package pick up, for employee lockers, or evidence storage users will always have an unrestricted view of the interior. Fully assembled and all welded 3 door heavy duty storage lockers. 1 1/4" x 1 1/4" x 1/8" angle frame work, 13 gauge shelves, 2" x 1" 10 gauge woven wire mesh sides. Units have 21" between shelves and doors are equipped with separate padlock lugs (Padlock sold separately). 1500 pound total capacity, 500 pounds per shelf when evenly distributed. Unit is painted dark gray. Units are non-returnable.



model JVSL-1818

MODEL NUMBER	OVERALL SIZE (W x D x H)	NUMBER OF SHELVES	WEIGHT (POUND)
JVSL-1818	18" x 18" x 75"	3	161
JVSL-2424	24" x 24" x 75"	3	210
JVSL-3030	30" x 30" x 75"	3	256
JVSL-3636	36" x 36" x 75"	3	314

Stainless Steel Lockers

Our 304 Stainless Steel Lockers are the perfect solution for areas prone to rust and sanitation concerns and are ideal for food industry, pool area, and outdoor applications. Ships knocked down, some assembly required. Other styles available, contact factory.

MODEL NUMBER	NUMBER OF COLUMNS	NUMBER OF ROWS	NUMBER OF LOCKERS	OVERALL SIZE (W x D x H)	WEIGHT (POUND)
LOCK-1218-SSS1*	1	1	1	12" x 18" x 78"	62
LOCK-1818-SSS1**	1	1	1	18" x 18" x 78"	79
LOCK-3618-SSS3	3	1	3	36" x 18" x 78"	168
LOCK-5418-SSS3	3	1	3	54" x 18" x 78"	219
LOCK-1218-SSD1*	1	2	2	12" x 18" x 78"	64
LOCK-1818-SSD1**	1	2	2	18" x 18" x 78"	79
LOCK-3618-SSD3	3	2	6	36" x 18" x 78"	174
LOCK-5418-SSD3	3	2	6	54" x 18" x 78"	219
LOCK-1218-SS61	1	6	6	12" x 18" x 78"	74
LOCK-1818-SS61	1	6	6	18" x 18" x 78"	96
LOCK-3618-SS63	3	6	18	36" x 18" x 78"	216
LOCK-5418-SS63	3	6	18	54" x 18" x 78"	270
LOCK-CR-12	*12" COAT ROD (available in 1 & 2 rows only)				1
LOCK-CR-18	**18" COAT ROD (available in 1 & 2 rows only)				2



model
LOCK-3618-SSD3



model
LOCK-3618-SS63

Heavy Duty Electric Fuel Pumps

Heavy duty industrial grade fuel pumps are designed for everyday use in agriculture, construction, automotive, and industrial applications. Rain and weather proof for outdoor applications. Lightweight, yet strong, non-corroding aluminum die cast construction. Geared design makes the pump tolerant to contaminants in fuel. cUL listed motor. Duty cycle: 30 minutes ON / 30 minutes OFF. Recommended use: Gasoline, Diesel, E15 Fuel, Kerosene, Bio Diesel (B20).

MODEL NUMBER	VOLTAGE	FLOW RATE (AT PUMP OUTLET)	INLET / OUTLET	WEIGHT (POUND)
PUMP-HDE-12	12V DC	UP TO 15 GPM	1" NPT / 3/4" NPT	30
PUMP-HDE-115	115V AC	UP TO 13 GPM	1" NPT / 3/4" NPT	30



HDE series

Heavy Duty High Flow Electric Fuel Pump

Heavy duty industrial grade high flow fuel pump is designed for everyday use in agriculture, construction, automotive, and industrial applications. Rain and weather proof for outdoor applications. Lightweight, yet strong, non-corroding aluminum die cast construction. Geared design makes the pump tolerant to contaminants in fuel. cUL listed motor. Duty cycle: 30 minutes ON / 30 minutes OFF. Recommended use: Gasoline, Diesel, E15 Fuel, Kerosene, Bio Diesel (B20).

MODEL NUMBER	VOLTAGE	FLOW RATE (AT PUMP OUTLET)	INLET / OUTLET	WEIGHT (POUND)
PUMP-HFE-12	12V DC	UP TO 20 GPM	1" NPT / 1" NPT	35



model
PUMP-HFE-12



model PUMP-E-12



model PUMP-E-12-ST

Electric Diesel Pumps

Portable diesel transfer pumps designed for everyday use in agriculture, construction, automotive, and industrial applications. Lightweight, yet strong, non-corroding aluminum die cast construction. Self-priming vane pump design. Base mounted and complete with lift handle. Includes hose barbs and a battery cable. Model PUMP-E-12-ST comes with suction and delivery hoses and a manual fuel control nozzle. Duty cycle: 30 minutes ON / 30 minutes OFF. Recommended use: Diesel, Kerosene.

MODEL NUMBER	VOLTAGE	FLOW RATE (AT PUMP OUTLET)	INLET / OUTLET	WEIGHT (POUND)
PUMP-E-12	12V DC	UP TO 12 GPM	3/4" NPT / 3/4" NPT	13
PUMP-E-12-ST	12V DC	UP TO 12 GPM	3/4" NPT / 3/4" NPT	17

Continuous Duty Pump

Diesel transfer pump is ideal for use on stationary tanks, fixed fuel transferring systems and dispensers, and other similar industrial applications. Lightweight, yet strong, non-corroding aluminum die cast construction. Self-priming vane pump. Continuous duty cycle with thermal overload protection. Contains a power cord with a US socket. Recommended use: Diesel, Kerosene.



model PUMP-CD-115

MODEL NUMBER	VOLTAGE	FLOW RATE (AT PUMP OUTLET)	INLET / OUTLET	WEIGHT (POUND)
PUMP-CD-115	115V AC	UP TO 15 GPM	1" NPT / 1" NPT	17

Electric DEF Pumps

Diaphragm transfer pump designed for dispensing DEF. Lightweight non-corroding polypropylene body that is rain and weather proof. Pump has a self-priming design and an inlet & outlet fitting with 3/4 hose barbs. Duty cycle: 30 minutes ON / 30 minutes OFF. Recommended use: DEF, Adblue, Urea, Water, Antifreeze, Detergents. Do not use: Diesel, Kerosene, Gasoline, Oils.



model PUMP-DEF-115

MODEL NUMBER	VOLTAGE	FLOW RATE	INLET / OUTLET	WEIGHT (POUND)
PUMP-DEF-12	12V DC	UP TO 9 GPM	3/4" HOSE BARB	14
PUMP-DEF-115	115V AC	UP TO 9 GPM	3/4" HOSE BARB	16

Electric Oil Pumps

Heavy duty oil pumps designed specifically to transfer bulk oils, hydraulic oils, antifreeze, or antifreeze mixes. Pump has a non-corroding aluminum die cast body. It also includes an internal bypass valve to bypass flow if discharge pressure exceeds bypass valve setting. Built-in 2" bung adaptor for mounting directly onto drums and tanks. Can also be used to transfer used oil. Just fitting a screen onto the suction tube makes it effective for transferring used oil. Recommended use: Oils, Synthetic Oils, Antifreeze, Used Oils, Hydraulic Fluids, Cutting Oils, Oil Based Herbicides, Non-flammable Oil Based Solvents, Liquid Soap.



model PUMP-EO-12



model PUMP-EO-115

MODEL NUMBER	VOLTAGE	FLOW RATE	INLET / OUTLET	WEIGHT (POUND)
PUMP-EO-115	115V AC	UP TO 4.4 GPM	1" NPT / 3/4" NPT	39
PUMP-EO-115-HF*	115V AC	UP TO 8 GPM	1" NPT / 3/4" NPT	41
PUMP-EO-12	12V DC	UP TO 3.5 GPM	1" NPT / 3/4" NPT	30

*HF = HIGH FLOW

Sign Stands

Display your signs anywhere. Surface mounted with a weighted base. Includes (3) three holes, 9/16" diameter with 1 3/8" diameter counter-bore for permanent mounting of sign. Removable post will accept virtually any sign (signs available, pages 80-92). Available with or without wheels. Wheels allow you to tip and roll unit. Steel construction.

MODEL NUMBER	DESCRIPTION	HEIGHT	BASE DIAMETER	WEIGHT (POUND)
S-STAND [®]	NO WHEELS	48"	18"	17
S-STAND-W [®]	WHEELS INCLUDED	48"	18"	22
AS-125 [®]	ANCHOR BOLTS (1) 1/2" x 5", (3) BOLTS NEEDED			1



Sign Base Systems

Give your property that brand new look for years to come! Save time on installation and no core drilling or anchor assembly required. Pyramid base can be conveniently rolled out of the way for parking lot maintenance and snow removal. Made with 1/4" low density polyethylene, which has ultra-violet and anti-static additives for long lasting, maintenance free use. Bases can be filled with concrete, sand, or up to twenty two (22) gallons of water (11 1/2 gallons model OSB). Steel pipe sleeved with high-density thermoplastic included with bases. Supports various signs (pages 80-92) from "NO PARKING", to "STOP SIGN", and post is removable from base for easy storage.

MODEL NUMBER	BASE DIMENSIONS (W x D x H)	WHEELS	OVERALL HEIGHT	POST DIAMETER	COLOR	WEIGHT (POUND)
PYSB-Y	22" x 22" x 22"	NO	98"	1.6"	YELLOW	46
PYSB-R	22" x 22" x 22"	NO	98"	1.6"	RED	46
PYSB-B	22" x 22" x 22"	NO	98"	1.6"	BLUE	46
PYSB-BK	22" x 22" x 22"	NO	98"	1.6"	BLACK	46
PYSB-W-Y	22" x 22" x 22"	YES	98"	1.6"	YELLOW	46
PYSB-W-R	22" x 22" x 22"	YES	98"	1.6"	RED	46
PYSB-W-B	22" x 22" x 22"	YES	98"	1.6"	BLUE	46
PYSB-W-BK	22" x 22" x 22"	YES	98"	1.6"	BLACK	46
OSB-R	8"W side x 20"H base	NO	98"	1.6"	RED	46
OSB-B	8"W side x 20"H base	NO	98"	1.6"	BLUE	46
OSB-GN	8"W side x 20"H base	NO	98"	1.6"	GREEN	46



Portable & Permanent Sign Bases

Sign Bases are perfect for parking garages, parking lots, retail establishments, school crossings, and high traffic pedestrian walkways. A lightweight and more durable option to steel, these signs are designed to take vehicle impacts and low speed roll-overs without causing damage to the post or vehicle. The recycled base, series FSP-BASE, is perfect for short term applications or when a rapid deployment is necessary. Permanent sign posts with circular bases can be anchored with 1/4" lag bolts (not included). Other post heights and signs are available, contact factory for pricing. For more bases and posts please see *Protective Barriers* section. Signs available on pages 80-92.

MODEL NUMBER	OVERALL HEIGHT	POST DIAMETER	COLOR	WEIGHT (POUND)
PORTABLE SIGN POSTS (ONLY)				
FSP-24-O	24"	2"	ORANGE	1
FSP-24-Y	24"	2"	YELLOW	1
FSP-24-W	24"	2"	WHITE	1
FSP-36-O	36"	2"	ORANGE	1
FSP-36-Y	36"	2"	YELLOW	1
FSP-36-W	36"	2"	WHITE	1
FSP-48-O	48"	2"	ORANGE	1
FSP-48-Y	48"	2"	YELLOW	1
FSP-48-W	48"	2"	WHITE	1
PORTABLE SIGN POST BASES & INSERT				
FSP-BASE-L	LARGE BASE WITH HANDLE (30"W x 14"L x 2"H)			33
FSP-INSERT	TUBULAR FLEX INSERT ONLY			1
PERMANENT SIGN POSTS WITH CIRCULAR BASE (ANCHOR HARDWARE NOT INCLUDED)				
FSP-24-O-PS	24"	2"	ORANGE	3
FSP-24-Y-PS	24"	2"	YELLOW	3
FSP-24-W-PS	24"	2"	WHITE	3
FSP-36-O-PS	36"	2"	ORANGE	3
FSP-36-Y-PS	36"	2"	YELLOW	3
FSP-36-W-PS	36"	2"	WHITE	3
FSP-48-O-PS	48"	2"	ORANGE	3
FSP-48-Y-PS	48"	2"	YELLOW	3
FSP-48-W-PS	48"	2"	WHITE	3



PORTABLE SIGN POST, model FSP-24-W
BASE & INSERT, model FSP-BASE-L
TUBULAR FLEX INSERT, model FSP-INSERT



model FSP-BASE-L model FSP-36-W-PS

Introducing Our **NEW** Industrial Signage Solutions

About Our Print On Demand Signage Process

Print On Demand allows Vestil to keep fewer, less popular industrial and OSHA signs in stock, further reducing storage space and handling costs. And because your inventory levels can be kept low, Print On Demand helps reduce the chance of being left with product that has become obsolete. With our Print On Demand sign manufacturing process, we are able to react to your demand quickly. Our technology is also environmentally friendly.

Ask Us About Our Unique Two-Sided Bilingual Signage



Many other sign materials are available!

- Plastics
- Metals
- Reflective Aluminum
- Glow-in-the-Dark

We Use UV Ink Technology

With the increasing demand for quick turnaround on production runs, Vestil has adapted the use of UV ink devices that were developed specifically for the signage industry. These inks are formulated to cure quickly and offer many years of outdoor durability, as well as resistance to water and abrasion. The inks are applied directly to the substrate, thus eliminating costly additional labor traditionally associated with other sign manufacturing.



Safety Sign Categories

- Chemicals & Haz-Mat
- Entrance & Exit
- Construction
- Fire and Emergency
- Electrical and Many More!



ONLINE CUSTOM DESIGNER

Vestil can affiliate integration to our internet web-to-print solution allowing for direct customization of all types of industrial signage.

OUR SIGNAGE IS MADE TO LAST!



Anti-Graffiti Coating!

Anti-Graffiti is made with Tedlar®, providing an extremely durable polyvinyl fluoride (PVF) film surface for use as an anti-graffiti film. It is washable and resistant to a large number of detergents and solvents. This film provides excellent UV protection. Anti-Graffiti is recommended for both outdoor and indoor applications. UV light inhibitors aid in stopping discoloration from the Sun.

Sign Material Choices



Economy Value

.011 Vinyl Label Decal Sign

For general labeling or extreme conditions; Vinyl labels offer moisture, chemical, and UV resistance making them ideal for labeling indoors. If you're looking for a economical solution that's easy to apply to most surfaces then vinyl adhesive is your answer.



Economy Value

.040 Polystyrene Sign

Polystyrene signs are the ideal sign choice for indoor signage. We offer polystyrene signs in .040" gauge thickness. This material is made from a form of plastic and long lasting when used indoors. If your business or school needs indoor signage or directional signage, then polystyrene is the solution.



Standard Value

.040, .063, & .080 Aluminum Sign

Aluminum never rusts. Aluminum withstands wash-downs, harsh elements, abusive conditions, and feature good chemical, abrasion, and impact resistance. Aluminum is excellent for indoor and outdoor usage, making it ideal for a wide variety of industrial strength applications.

- Standard Thicknesses are .040", .063", & .080"
- Protected by UV resistant clear *Anti-Graffiti coating!*
- Withstands harsh cleanings
- Endures outdoor environmental conditions
- Service temperature range -40° to 250°F
- Signs are round cornered and provided with holes for mounting
- Signage - Exterior long-term application life



Premium Value

.130 Aluminum (ACM) Sign

Aluminum composite material (ACM) is comprised of two pre-painted sheets of .130" aluminum with a solid polyethylene core. Provides excellent durability in outdoor applications, is lightweight, and is approximately one half the weight of our aluminum signs. Won't bow or warp. Interior or exterior long-term application life. Made In USA.

With *Anti-Graffiti coating!*



Made to Last

Our safety signs are available in all popular sizes including oversized, colors, or shapes. Vestil assures that all signs will exceed consumer expectations. All of our signs are imaged using our state-of-the-art Print On Demand process with UV inks that won't dissolve or fade over time.

Anti-Graffiti UV Laminate is applied over the surface of all our aluminum constructed signs to prevent fading & increase longevity. Also available as a option on other available materials.

Our categories of signs include safety signs, security signs, first aid signs, safety banners, and many more.

You can get all of the signage you'll ever need to hang throughout your warehouse and facility including ANSI signs, OSHA signs, warning signs, danger signs, caution signs, notice signs, and more.



NOTICE SAFETY SIGNAGE

OUR MOST POPULAR REQUESTED Signs!



SI-N-01



NOTICE Model Number Format:

(sign #) - (size) - (material)

Example: SI-N-01-A-AL-040

When ordering your signage follow these steps:

STEP 1 - Select your sign number.

STEP 2 - Select your size:

(A) 10.5" x 7.5" (B) 12.5" x 9.5" (C) 14.5" x 10.5"

(D) 18.5" x 12.5" (E) 20.5" x 14.5"

STEP 3 - Select your material:

(AL-040) .040" Aluminum Sign

(AL-063) .063" Aluminum Sign

(AL-080) .080" Aluminum Sign

(AC-130) .130" Aluminum Composite (ACM) Sign

(PS-040) .040" Polystyrene Sign

(LB-011) .011" Vinyl Label Decal Sign

All signs will receive installation kits.



SI-N-02



SI-N-03



SI-N-04



SI-N-05



SI-N-06



SI-N-07



SI-N-08



SI-N-09



SI-N-10



SI-N-11



SI-N-12



SI-N-13



SI-N-14



SI-N-15



SI-N-16



SI-N-17



SI-N-18



SI-N-19




SI-N-20



SI-N-21



SI-N-22



SI-N-23



SI-N-24



SI-N-25



SI-N-26



SI-N-27



SI-N-28



SI-N-29



SI-N-30



SI-N-31



SI-N-32



SI-N-33



SI-N-34



SI-N-35



SI-N-36



SI-N-37



SI-N-38



SI-N-039



SI-N-40



SI-N-41



SI-N-42



SI-N-43



SI-N-44



SI-N-45



SI-N-46



SI-N-47



SI-N-48



SI-N-49



SI-N-50



SI-N-51



SI-N-52



SI-N-53



SI-N-54



SI-N-55



SI-N-56



SI-N-57



SI-N-58



SI-N-59



SI-N-60



SI-N-61



SI-N-62



SI-N-63



SI-N-64



SI-N-65



SI-N-66



SI-N-67



SI-N-68



SI-N-69



SI-N-70

DANGER SAFETY SIGNAGE

OUR MOST POPULAR REQUESTED Signs!



SI-D-01



DANGER Model Number Format:

(sign #) - (size) - (material)

Example: SI-D-01-E-LB-011

When ordering your signage follow these steps:

STEP 1 - Select your sign number.

STEP 2 - Select your size:

(A) 10.5" x 7.5" (B) 12.5" x 9.5" (C) 14.5" x 10.5"

(D) 18.5" x 12.5" (E) 20.5" x 14.5"

STEP 3 - Select your material:

(AL-040) .040" Aluminum Sign

(AL-063) .063" Aluminum Sign

(AL-080) .080" Aluminum Sign

(AC-130) .130" Aluminum Composite (ACM) Sign

(PS-040) .040" Polystyrene Sign

(LB-011) .011" Vinyl Label Decal Sign

All signs will receive installation kits.



SI-D-02



SI-D-03



SI-D-04



SI-D-05



SI-D-06



SI-D-07



SI-D-08



SI-D-09



SI-D-10



SI-D-11



SI-D-12



SI-D-13



SI-D-14



SI-D-15



SI-D-16



SI-D-17



SI-D-18



SI-D-19



SI-D-20




SI-D-21



SI-D-22



SI-D-23



SI-D-024



SI-N-25



SI-D-26



SI-D-27



SI-D-28



SI-D-29



SI-D-30



SI-D-31



SI-D-32



SI-D-33



SI-D-34



SI-D-35



SI-D-36



SI-D-37



SI-D-38



SI-D-39



SI-D-40



SI-D-41



SI-D-42



SI-D-43



SI-D-44



SI-D-45



SI-D-46



SI-D-47



SI-D-48



SI-D-49



SI-D-50



SI-D-51



SI-D-52



SI-D-53



SI-D-54



SI-D-55



SI-D-56



SI-D-57



SI-D-58



SI-D-59



SI-D-60



SI-D-61



SI-D-62



SI-D-63



SI-D-64



SI-D-65



SI-D-66



SI-D-67



SI-D-68



SI-D-69



SI-D-70

WARNING SAFETY SIGNAGE

OUR MOST POPULAR REQUESTED Signs!



SI-W-01



WARNING Model Number Format:

(sign #) - (size) - (material)

Example: SI-W-01-C-PS-040

When ordering your signage follow these steps:

STEP 1 - Select your sign number.

STEP 2 - Select your size:

- (A) 10.5" x 7.5" (B) 12.5" x 9.5" (C) 14.5" x 10.5"
- (D) 18.5" x 12.5" (E) 20.5" x 14.5"

STEP 3 - Select your material:

- (AL-040) .040" Aluminum Sign
- (AL-063) .063" Aluminum Sign
- (AL-080) .080" Aluminum Sign
- (AC-130) .130" Aluminum Composite (ACM) Sign
- (PS-040) .040" Polystyrene Sign
- (LB-011) .011" Vinyl Label Decal Sign

All signs will receive installation kits.



SI-W-02



SI-W-03



SI-W-04



SI-W-05



SI-W-06



SI-W-07



SI-W-08



SI-W-09



SI-W-10



SI-W-11



SI-W-12



SI-W-13



SI-W-14



SI-W-15



SI-W-16



SI-W-17



SI-W-18



SI-W-19



SI-W-20



SI-W-21



SI-W-22



SI-W-23



SI-W-24



SI-W-25



SI-W-26



SI-W-27



SI-W-28



SI-W-29



SI-W-30



SI-W-31



SI-W-32



SI-W-33



SI-W-34



SI-W-35



SI-W-36



SI-W-37



SI-W-38



SI-W-39



SI-W-40



SI-W-41



SI-W-42



SI-W-43



SI-W-44



SI-W-45



SI-W-46



SI-W-47



SI-W-48



SI-W-49



SI-W-50



SI-W-51



SI-W-52



SI-W-53



SI-W-54



SI-W-55



SI-W-56



SI-W-57



SI-W-58



SI-W-59



SI-W-60



SI-W-61



SI-W-62



SI-W-63



SI-W-64



SI-W-65



SI-W-66



SI-W-67



SI-W-68



SI-W-69



SI-W-70

CAUTION SAFETY SIGNAGE

OUR MOST POPULAR REQUESTED Signs!



SI-C-01



CAUTION Model Number Format:

(sign #) - (size) - (material)

Example: SI-C-01-B-AC-130

When ordering your signage follow these steps:

STEP 1 - Select your sign number.

STEP 2 - Select your size:

- (A) 10.5" x 7.5" (B) 12.5" x 9.5" (C) 14.5" x 10.5"
- (D) 18.5" x 12.5" (E) 20.5" x 14.5"

STEP 3 - Select your material:

- (AL-040) .040" Aluminum Sign
- (AL-063) .063" Aluminum Sign
- (AL-080) .080" Aluminum Sign
- (AC-130) .130" Aluminum Composite (ACM) Sign
- (PS-040) .040" Polystyrene Sign
- (LB-011) .011 Vinyl Label Decal Sign

All signs will receive installation kits.



SI-C-02



SI-C-03



SI-C-04



SI-C-05



SI-C-06



SI-C-07



SI-C-08



SI-C-09



SI-C-10



SI-C-11



SI-C-12



SI-C-13



SI-C-14



SI-C-15



SI-C-16



SI-C-17



SI-C-18



SI-C-19



SI-C-20



SI-C-21



SI-C-22



SI-C-23



SI-C-24



SI-C-25



SI-C-26



SI-C-27



SI-C-28



SI-C-29



SI-C-30



SI-C-31



SI-C-32



SI-C-33



SI-C-34



SI-C-35



SI-C-36



SI-C-37



SI-C-38



SI-C-39



SI-C-40



SI-C-41



SI-C-42



SI-C-43



SI-C-44



SI-C-45



SI-C-46



SI-C-47



SI-C-48



SI-C-49



SI-C-50



SI-C-51



SI-C-52



SI-C-53



SI-C-54



SI-C-55



SI-C-56



SI-C-57



SI-C-58



SI-C-59



SI-C-60



SI-C-61



SI-C-62



SI-C-63



SI-C-64



SI-C-65



SI-C-66



SI-C-67



SI-C-68



SI-C-69



SI-C-70

CAUTION SAFETY SIGNAGE

MOST POPULAR REQUESTED Signs!



SI-C-71



SI-C-72



SI-C-73



SI-C-74



SI-C-75



SI-C-76



SI-C-77



SI-C-78



SI-C-79



SI-C-80



FREE CUSTOMIZATION ON ALL OUR SIGNS!

Every sign shown on these catalog pages can be repurposed with our online sign builder. Visit mysigns.com to learn how.

We make it easy by providing hundreds of templates for you and allowing you to simply modify the artwork however you choose.

We also have a large library of safety pictographs for your use on your sign design for any application or work environment.



***Our Online Store
Is Like No Other!***

Model Number Format:**SI - (type - C, D, W, N) - (sign #) - (size) - (material)***Example: SI-C-01-B-AC-130***Industrial Signage
Ordering Information***All signs will receive installation kits.***When ordering your signage follow these steps:****STEP 1 - Select your sign number.****STEP 2 - Select your size:**(A) 10.5" x 7.5" (B) 12.5" x 9.5" (C) 14.5" x 10.5"
(D) 18.5" x 12.5" (E) 20.5" x 14.5"**STEP 3 - Select your material:**(AL-040) .040" Aluminum Sign
(AL-063) .063" Aluminum Sign
(AL-080) .080" Aluminum Sign
(AC-130) .130" Aluminum Composite (ACM) Sign
(PS-040) .040" Polystyrene Sign
(LB-011) .011" Vinyl Label Decal Sign

MODEL NUMBER	SIGN TYPE*	OVERALL SIZE (W x H)	WEIGHT (POUND)
.040" COATED ALUMINUM WITH UV PROTECTION			
SI - (C, D, W, N*) - SIGN # - A - AL-040	CAUTION / DANGER / WARNING / NOTICE	(A) 10.5" x 7.5"	1
SI - (C, D, W, N*) - SIGN # - B - AL-040	CAUTION / DANGER / WARNING / NOTICE	(B) 12.5" x 9.5"	2
SI - (C, D, W, N*) - SIGN # - C - AL-040	CAUTION / DANGER / WARNING / NOTICE	(C) 14.5" x 10.5"	3
SI - (C, D, W, N*) - SIGN # - D - AL-040	CAUTION / DANGER / WARNING / NOTICE	(D) 18.5" x 12.5"	4
SI - (C, D, W, N*) - SIGN # - E - AL-040	CAUTION / DANGER / WARNING / NOTICE	(E) 20.5" x 14.5"	4
.063" COATED ALUMINUM WITH UV PROTECTION			
SI - (C, D, W, N*) - SIGN # - A - AL-063	CAUTION / DANGER / WARNING / NOTICE	(A) 10.5" x 7.5"	1
SI - (C, D, W, N*) - SIGN # - B - AL-063	CAUTION / DANGER / WARNING / NOTICE	(B) 12.5" x 9.5"	2
SI - (C, D, W, N*) - SIGN # - C - AL-063	CAUTION / DANGER / WARNING / NOTICE	(C) 14.5" x 10.5"	3
SI - (C, D, W, N*) - SIGN # - D - AL-063	CAUTION / DANGER / WARNING / NOTICE	(D) 18.5" x 12.5"	4
SI - (C, D, W, N*) - SIGN # - E - AL-063	CAUTION / DANGER / WARNING / NOTICE	(E) 20.5" x 14.5"	4
.080" COATED ALUMINUM WITH UV PROTECTION			
SI - (C, D, W, N*) - SIGN # - A - AL-080	CAUTION / DANGER / WARNING / NOTICE	(A) 10.5" x 7.5"	1
SI - (C, D, W, N*) - SIGN # - B - AL-080	CAUTION / DANGER / WARNING / NOTICE	(B) 12.5" x 9.5"	2
SI - (C, D, W, N*) - SIGN # - C - AL-080	CAUTION / DANGER / WARNING / NOTICE	(C) 14.5" x 10.5"	3
SI - (C, D, W, N*) - SIGN # - D - AL-080	CAUTION / DANGER / WARNING / NOTICE	(D) 18.5" x 12.5"	4
SI - (C, D, W, N*) - SIGN # - E - AL-080	CAUTION / DANGER / WARNING / NOTICE	(E) 20.5" x 14.5"	4
.130" PREMIUM ALUMINUM COMPOSITE (ACM) WITH UV PROTECTION			
SI - (C, D, W, N*) - SIGN # - A - AC-130	CAUTION / DANGER / WARNING / NOTICE	(A) 10.5" x 7.5"	1
SI - (C, D, W, N*) - SIGN # - B - AC-130	CAUTION / DANGER / WARNING / NOTICE	(B) 12.5" x 9.5"	2
SI - (C, D, W, N*) - SIGN # - C - AC-130	CAUTION / DANGER / WARNING / NOTICE	(C) 14.5" x 10.5"	3
SI - (C, D, W, N*) - SIGN # - D - AC-130	CAUTION / DANGER / WARNING / NOTICE	(D) 18.5" x 12.5"	4
SI - (C, D, W, N*) - SIGN # - E - AC-130	CAUTION / DANGER / WARNING / NOTICE	(E) 20.5" x 14.5"	4
.040" POLYSTYRENE			
SI - (C, D, W, N*) - SIGN # - A - PS-040	CAUTION / DANGER / WARNING / NOTICE	(A) 10.5" x 7.5"	1
SI - (C, D, W, N*) - SIGN # - B - PS-040	CAUTION / DANGER / WARNING / NOTICE	(B) 12.5" x 9.5"	2
SI - (C, D, W, N*) - SIGN # - C - PS-040	CAUTION / DANGER / WARNING / NOTICE	(C) 14.5" x 10.5"	2
SI - (C, D, W, N*) - SIGN # - D - PS-040	CAUTION / DANGER / WARNING / NOTICE	(D) 18.5" x 12.5"	3
SI - (C, D, W, N*) - SIGN # - E - PS-040	CAUTION / DANGER / WARNING / NOTICE	(E) 20.5" x 14.5"	4
.011" INDOOR/OUTDOOR VINYL LABEL (PERMANENT ADHESIVE)**			
SI - (C, D, W, N*) - SIGN # - A - LB-011	CAUTION / DANGER / WARNING / NOTICE	(A) 10.5" x 7.5"	1
SI - (C, D, W, N*) - SIGN # - B - LB-011	CAUTION / DANGER / WARNING / NOTICE	(B) 12.5" x 9.5"	1
SI - (C, D, W, N*) - SIGN # - C - LB-011	CAUTION / DANGER / WARNING / NOTICE	(C) 14.5" x 10.5"	1
SI - (C, D, W, N*) - SIGN # - D - LB-011	CAUTION / DANGER / WARNING / NOTICE	(D) 18.5" x 12.5"	2
SI - (C, D, W, N*) - SIGN # - E - LB-011	CAUTION / DANGER / WARNING / NOTICE	(E) 20.5" x 14.5"	2

*Specify sign type ("C" Caution, "D" Danger, "W" Warning or "N" Notice).

**Vinyl label adhesive is permanent and adheres to most smooth clean surfaces, indoor or outdoor applications.

Signs are provided with four (4) .25 inch diameter punched holes located in corners for mounting (labels not included). Other configurations available.

SAFETY SIGNAGE *How to Order - It's Simple!*

Available Materials



.040" Coated Aluminum - It's a flat, rigid metal substrate that is lightweight with a baked enamel finish made to withstand the elements for long-term outdoor and indoor use. Our custom aluminum signs are also available in many standard sizes and colors. Our custom aluminum signs are generally used for commercial, industrial, informational, and directional signage. It can be used with many different frame systems and will not rust.

.040" Polystyrene - Is one of the most widely used plastics. It is a rigid sheet of plastic. It is durable, low moisture resistance, and has good impact strength. Uses: Long-term indoor or short-term outdoor uses.

3 mm Premium Composite Aluminum (ACM) - A lightweight aluminium composite 3mm board, which is flat and rigid making it ideal for signage, display, presentation, and point of sale applications. It is corrosion resistant and very stable to changes in temperature, making it ideal for outdoor signage. The black core is UV stable and will not warp or delaminate.

Vinyl Pressure Sensitive label - Our least expensive option. Can be used on any clean smooth surface, indoor or outdoor applications.



All of our OSHA basic signs come in extended sizes so you get the most from your space and purchase.



Each sign is carefully manufactured to ensure long-life.



Don't see what you want exactly, visit us online at www.myvsigns.com to CUSTOMIZE ALL of these messages or choose and customize from hundreds of others designs!